

View Online at <https://aerobasegroup.com/nsn/5955-01-482-3928>

Overall Length:

Between 0.295 inches and 0.300 inches

Overall Diameter:

Between 0.405 inches and 0.410 inches

Operating Temperature Range:

-55.0/+105.0 degrees celsius

Storage Temperature Range:

-62.0/+125.0 degrees celsius

Average Life Measurement:

Not rated

End Application:

F-16 brake control/anti. Skid

Basic Shape Style:

Cylindrical

Inclosure Type:

Hermetically sealed

Operating Control Method:

Automatic

Installation Design:

Module

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Per Channel:

30.0 megahertz output channel

Connection Type And Location:

Err-060 glad hand quick disconnect

Connection Contact Type And Quantity:

8 liters of liquid nitrogen drain

External Dc Operating Voltage In Volts:

4.5 single voltage and 5.5 single voltage

Special Features:

Pin length is min.0.480

Test Data Document:

81349-mil-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-prf-55310/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200

Mil-std (military Standard):

Mil-prf-55310 spec.