

View Online at <https://aerobasegroup.com/nsn/5955-01-482-3928>

**Overall Length:**

Between 0.295 inches and 0.300 inches

**Overall Diameter:**

Between 0.405 inches and 0.410 inches

**Operating Temperature Range:**

-55.0/+105.0 degrees celsius

**Storage Temperature Range:**

-62.0/+125.0 degrees celsius

**Average Life Measurement:**

Not rated

**End Application:**

F-16 brake control/anti. Skid

**Basic Shape Style:**

Cylindrical

**Inclosure Type:**

Hermetically sealed

**Operating Control Method:**

Automatic

**Installation Design:**

Module

**Control Type:**

Local

**Circuit Construction Type:**

Solid state

**Frequency Per Channel:**

30.0 megahertz output channel

**Connection Type And Location:**

Err-060 glad hand quick disconnect

**Connection Contact Type And Quantity:**

8 liters of liquid nitrogen drain

**External Dc Operating Voltage In Volts:**

4.5 single voltage and 5.5 single voltage

**Special Features:**

Pin length is min.0.480

**Test Data Document:**

81349-mil-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-prf-55310/9 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A32200

**Mil-std (military Standard):**

Mil-prf-55310 spec.