## NSN 5955-01-482-9597

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-482-9597 **Overall Length:** 0.887 inches **Overall Height:** 0.400 inches **Overall Width:** 0.540 inches **Environmental Protection:** Shock resistant and vibration **Operating Tempurature Range:** -55.0/+105.0 degrees celsius Storage Tempurature Range: -62.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** Identify friend or foe (iff); wsd: aircraft, awacs, e-3a **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Circuit Construction Type:** Solid state **Connection Type And Location:** Pin bottom **Connection Contact Type And Quantity:** 14 pin external **External Dc Operating Voltage In Volts:** 4.5 single voltage and 5.5 single voltage **Test Data Document:** 81349-mil-prf-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-prf-55310/16b41b44-13790 government specification Shelf Life: N/a **Unit Of Measure:** 

Yes - demil/mli

**Demilitarization:** 

## NSN 5955-01-482-9597

Crystal Controlled Oscillator - Page 2 of 2



Fiig:

A32200

Mil-std (military Standard):

Mil-prf-55310 spec.