## NSN 5955-01-483-2507

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-483-2507 **Overall Length:** 0.887 inches **Overall Height:** 0.400 inches **Overall Width:** 0.540 inches **Environmental Protection:** Moisture proof **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -62.0/+125.0 degrees celsius **Average Life Measurement:** Not rated **End Application:** Panel, interface dev (p/n 263031001tph-1 pcc: gnz); e-nsn isil; cca **Basic Shape Style:** Rectangular or square **Inclosure Type:** Hermetically sealed **Operating Control Method:** Automatic Installation Design: Module **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 44.5 kilohertz output channel err-100 **External Dc Operating Voltage In Volts:** 4.5 single voltage and 5.5 single voltage **Special Features:** height includes 2.00 in. Pin length **Test Data Document:** 81349-mil-prf-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349 - mil-prf-55310/14 government specification Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5955-01-483-2507

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200

Mil-std (military Standard):

Mil-prf-55310 spec.