Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-485-6786

Ove	rall Length:
	7 inches
	rall Height:
	0 inches
	rall Width:
	0 inches
	rating Tempurature Range:
-	D/+125.0 degrees celsius
	rage Tempurature Range:
	D/+125.0 degrees celsius
	rage Life Measurement:
	rated
End	Application:
	sy-s depo; seawolf class ssn
	ic Shape Style:
Rect	tangular or square
Incl	osure Type:
Herr	netically sealed
Оре	rating Control Method:
Auto	omatic
Inst	allation Design:
Mod	lule
Con	trol Type:
Rem	note
Circ	uit Construction Type:
Solid	d state
Frec	quency Per Channel:
3.68	6 megahertz operating channel
Con	nection Type And Location:
Err-(060 glad hand quick disconnect
Con	nection Contact Type And Quantity:
14 li	ters of liquid nitrogen drain
Exte	ernal Dc Operating Voltage In Volts:
4.5	single voltage and 5.5 single voltage
Spe	cial Features:
heig	ght includes 0.200 in. Pin length
Test	t Data Document:
8134	49-mil-prf-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
form	at; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-prf-55310/18 government specification

Shelf Life:

N/a

Crystal Controlled Oscillator - Page 2 of 2



Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A32200

Mil-std (military Standard):

Mil-prf-55310 spec.