## NSN 5955-01-485-6812

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-485-6812

Overall	Length	1:
D - 4	- 0 005	

Between 0.635 inches and 0.665 inches

**Overall Height:** 

0.085 inches

Overall Width:

Between 0.635 inches and 0.665 inches

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Storage Tempurature Range:** 

-62.0/+125.0 degrees celsius

**Average Life Measurement:** 

Not rated

**End Application:** 

An/bsy-2 depo; wsd: seawolf class ssn

**Basic Shape Style:** 

Rectangular or square

**Inclosure Type:** 

Hermetically sealed

**Operating Control Method:** 

Automatic

Installation Design:

Module

**Control Type:** 

Remote

**Circuit Construction Type:** 

Solid state

**Frequency Per Channel:** 

1.320 megahertz operating channel

**Connection Type And Location:** 

Err-060 unthreaded universal fitting bolt end and err-060 threaded internal and err-060 flanged and err-060 yoke

**Connection Contact Type And Quantity:** 

44 liters of liquid nitrogen drain

**External Dc Operating Voltage In Volts:** 

4.5 single voltage and 5.5 single voltage

**Test Data Document:** 

81349-mil-prf-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-prf-55310/20 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5955-01-485-6812

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

No

Fiig:

A32200

Mil-std (military Standard):

Mil-prf-55310 spec.