NSN 5955-01-485-6824

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-485-6824

Overall Length:
Between 0.635 inches and 0.665 inches
Overall Height:
0.085 inches
Overall Width:
Between 0.635 inches and 0.665 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-62.0/+125.0 degrees celsius
Average Life Measurement:
Not rated
End Application:
An/bsy-2 depo; wsd: seawolf class ssn
Basic Shape Style:
Rectangular or square
Inclosure Type:
Hermetically sealed
Operating Control Method:
Automatic
Installation Design:
Module
Control Type:
Remote
Circuit Construction Type:
Solid state
Frequency Per Channel:
1.400 megahertz operating channel
Connection Type And Location:
Err-060 unthreaded universal fitting bolt end and err-060 threaded internal and err-060 flanged and err-060 yoke
Connection Contact Type And Quantity:
44 liters of liquid nitrogen drain
External Dc Operating Voltage In Volts:
4.5 single voltage and 5.5 single voltage
Test Data Document:
81349-mil-prf-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-prf-55310/20 government specification
Shelf Life:

--

N/a

Unit Of Measure:

NSN 5955-01-485-6824

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200

Mil-std (military Standard):

Mil-prf-55310 spec.