A32200

Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-495-0854

| Overall Length: | |
|---|-----------------------|
| 0.887 inches | |
| Overall Height: | |
| 0.400 inches | |
| Overall Width: | |
| 0.540 inches | |
| Environmental Protection: | |
| Vibration | |
| Operating Tempurature Range: | |
| -55.0/+125.0 degrees celsius | |
| Average Life Measurement: | |
| Not rated | |
| End Application: | |
| Nsn: 6625-01-324-1523, test station, electrical-electronic equipment | |
| Basic Shape Style: | |
| Rectangular or square | |
| Inclosure Type: | |
| Hermetically sealed | |
| Installation Design: | |
| Module | |
| Circuit Construction Type: | |
| Solid state | |
| Frequency Per Channel: | |
| 10.0 kilohertz operating channel | |
| Connection Type And Location: | |
| Pin bottom | |
| Connection Contact Type And Quantity: | |
| 14 pin external | |
| External Dc Operating Voltage In Volts: | |
| 5.0 single voltage | |
| Test Data Document: | |
| 81349-mil-prf-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type of | lata in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type dat | a on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). | |
| Specification Data: | |
| 81349-mil-prf-55310/16 government specification | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |
| Fiig: | |
| | |

Crystal Controlled Oscillator - Page 2 of 2



Mil-std (military Standard):

Mil-prf-55310 spec.