Crystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-496-4197

(Overall Length:
(0.887 inches
(Overall Height:
(0.200 inches
(Overall Width:
(0.540 inches
(Operating Tempurature Range:
-	-55.0/+125.0 degrees celsius
4	Average Life Measurement:
I	Not rated
I	End Application:
	A05g0515-3, next assemblies a06g2509 dash nos. 3401 and 3402, used on a03g0100-1, wsd: aircraft, eagle f-15
I	Basic Shape Style:
I	Rectangular or square
I	Inclosure Type:
I	Hermetically sealed
(Operating Control Method:
	Automatic
I	Installation Design:
I	Module
(Control Type:
I	Remote
(Circuit Construction Type:
;	Solid state
I	Frequency Per Channel:
	11.059 megahertz operating channel
(Connection Type And Location:
I	Pin bottom
(Connection Contact Type And Quantity:
	14 pin external
I	External Dc Operating Voltage In Volts:
4	4.5 single voltage and 5.5 single voltage
:	Special Features:
;	30 mamps input current maximum at 5.25 volt
-	Test Data Document:
ł	81349-mil-prf-55310 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
1	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
(environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
;	Specification Data:
8	81349-mil-prf-55310/16 government specification
:	Shelf Life:
I	N/a
I	Unit Of Measure:

Crystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200

Mil-std (military Standard):

Mil-prf-55310 spec.