NSN 5955-01-502-3921

Noncrystal Controlled Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-01-502-3921 **Reliability Indicator:** Established **Overall Length:** 101.6 millimeters **Overall Height:** 57.2 millimeters **Overall Width:** 76.2 millimeters **Operating Tempurature Range:** +0.0/+50.0 degrees celsius **Average Life Rating:** 50000.0 **Storage Tempurature Range:** -40.0/+71.0 degrees celsius **Average Life Measurement:** Hours **End Application:** Next assembly 9451605 used on rsts; wsd: defense meteorological satellite program (dmsp) **Basic Shape Style:** Irregular **Maximum Operating Altitude Rating:** 10000.0 feet **Inclosure Type:** Encased Installation Design: Mechanical **Circuit Construction Type:** Solid state Frequency Per Channel: 3.0 gigahertz output channel **Connection Type And Location:** Receptacle, coaxial right side **Connection Contact Type And Quantity:** 7 solder stud external **External Dc Operating Voltage In Volts:** 24.0 single voltage **Special Features:** 8 baseplate mounting thru-holes 3.6 millimeters diameter Shelf Life: N/a

Unit Of Measure:

NSN 5955-01-502-3921

Noncrystal Controlled Oscillator - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A32200