NSN 5960-00-501-2412

Electron Tube Retainer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5960-00-501-2412

Inside Diameter: 1.375 inches Overall Height: 0.750 inches Mounting Slot Width: 0.194 inches single mounting facility Mounting Slot Length: 0.312 inches single mounting facility Distance From Retainer Center To Centerline Of Mounting Facility: 0.306 inches Distance From Retainer Center To End Of Extended Clip: 1.563 inches Angle Between Mounting Facility And Tension Loop Centerlines In Deg: 120.0 Angle Between Mounting Facility And Loop Hinge Centerlines In Deg: 210.0 Accommodated Item Securing Device Type: Clamp Electron Tube Base Accommodated Diameter: +1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provided: Holding spur Material: Stainless steel Surface Treatment: Passivate Style Designator: Single foot, dip locked, tension clamp	
Overall Height: 0.750 inches Mounting Slot Width: 0.194 inches single mounting facility Mounting Slot Length: 0.312 inches single mounting facility Distance From Retainer Center To Centerline Of Mounting Facility: 0.906 inches Distance From Retainer Center To End Of Extended Clip: 1.563 inches Angle Between Mounting Facility And Tension Loop Centerlines In Deg: 120.0 Angle Between Mounting Facility And Loop Hinge Centerlines In Deg: 210.0 Accommodated Item Securing Device Type: Clamp Electron Tube Base Accommodated Diameter: +1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provided: Holding spur Material: Stainless steel Surface Treatment: Passivate Style Designator:	
0.750 inchesMounting Slot Width:0.194 inches single mounting facilityMounting Slot Length:0.312 inches single mounting facilityDistance From Retainer Center To Centerline Of Mounting Facility:0.906 inchesDistance From Retainer Center To End Of Extended Clip:1.563 inchesAngle Between Mounting Facility And Tension Loop Centerlines In Deg:120.0Angle Between Mounting Facility And Loop Hinge Centerlines In Deg:210.0Accommodated Item Securing Device Type:ClampElectron Tube Base Accommodated Diameter:+1.337/+1.377 inchesMounting Facility Type And Quantity:1 slot single mounting facilityHolding spurMaterial:Stainless steelSurface Treatment:PassivateStyle Designator:	
Mounting Slot Width: 0.194 inches single mounting facility Mounting Slot Length: 0.312 inches single mounting facility Distance From Retainer Center To Centerline Of Mounting Facility: 0.906 inches Distance From Retainer Center To End Of Extended Clip: 1.563 inches Angle Between Mounting Facility And Tension Loop Centerlines In Deg: 120.0 Angle Between Mounting Facility And Loop Hinge Centerlines In Deg: 210.0 Accommodated Item Securing Device Type: Clamp Electron Tube Base Accommodated Diameter: +1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provided: Holding spur Material: Stainless steel Surface Treatment: Passivate Style Designator:	
0.194 inches single mounting facility Mounting Slot Length: 0.312 inches single mounting facility Distance From Retainer Center To Centerline Of Mounting Facility: 0.906 inches Distance From Retainer Center To End Of Extended Clip: 1.563 inches Angle Between Mounting Facility And Tension Loop Centerlines In Deg: 120.0 Angle Between Mounting Facility And Loop Hinge Centerlines In Deg: 210.0 Accommodated Item Securing Device Type: Clamp Electron Tube Base Accommodated Diameter: +1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provided: Holding spur Material: Stainless steel Sufface Treatment: Passivate Style Designator:	
Mounting Slot Length: 0.312 inches single mounting facility Distance From Retainer Center To Centerline Of Mounting Facility: 0.906 inches Distance From Retainer Center To End Of Extended Clip: 1.563 inches Angle Between Mounting Facility And Tension Loop Centerlines In Deg: 120.0 Angle Between Mounting Facility And Loop Hinge Centerlines In Deg: 210.0 Accommodated Item Securing Device Type: Clamp Electron Tube Base Accommodated Diameter: +1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provided: Holding spur Material: Stainless steel Surface Treatment: Passivate Style Designator:	
0.312 inches single mounting facility Distance From Retainer Center To Centerline Of Mounting Facility: 0.906 inches Distance From Retainer Center To End Of Extended Clip: 1.563 inches Angle Between Mounting Facility And Tension Loop Centerlines In Deg: 120.0 Angle Between Mounting Facility And Loop Hinge Centerlines In Deg: 210.0 Accommodated Item Securing Device Type: Clamp Electron Tube Base Accommodated Diameter: +1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provided: Holding spur Material: Stainless steel Surface Treatment: Passivate Style Designator:	
Distance From Retainer Center To Centerline Of Mounting Facility:0.906 inchesDistance From Retainer Center To End Of Extended Clip:1.563 inchesAngle Between Mounting Facility And Tension Loop Centerlines In Deg:120.0Angle Between Mounting Facility And Loop Hinge Centerlines In Deg:210.0Accommodated Item Securing Device Type:ClampElectron Tube Base Accommodated Diameter:+1.337/+1.377 inchesMounting Facility Type And Quantity:1 slot single mounting facilityFeatures Provided:Holding spurMaterial:Stainless steelSurface Treatment:PassivateStyle Designator:	
0.906 inches Distance From Retainer Center To End Of Extended Clip: 1.563 inches Angle Between Mounting Facility And Tension Loop Centerlines In Deg: 120.0 Angle Between Mounting Facility And Loop Hinge Centerlines In Deg: 210.0 Accommodated Item Securing Device Type: Clamp Electron Tube Base Accommodated Diameter: +1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provide: Holding spur Material: Stainless steel Surface Treatment: Passivate Style Designator:	
Distance From Retainer Center To End Of Extended Clip: 1.563 inches Angle Between Mounting Facility And Tension Loop Centerlines In Deg: 120.0 Angle Between Mounting Facility And Loop Hinge Centerlines In Deg: 210.0 Accommodated Item Securing Device Type: Clamp Electron Tube Base Accommodated Diameter: +1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provided: Holding spur Material: Stainless steel Surface Treatment: Passivate Style Designator:	
 1.563 inches Angle Between Mounting Facility And Tension Loop Centerlines In Deg: 120.0 Angle Between Mounting Facility And Loop Hinge Centerlines In Deg: 210.0 Accommodated Item Securing Device Type: Clamp Electron Tube Base Accommodated Diameter: +1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provided: Holding spur Material: Stainless steel Surface Treatment: Passivate Style Designator: 	
Angle Between Mounting Facility And Tension Loop Centerlines In Deg:120.0Angle Between Mounting Facility And Loop Hinge Centerlines In Deg:210.0Accommodated Item Securing Device Type:ClampElectron Tube Base Accommodated Diameter:+1.337/+1.377 inchesMounting Facility Type And Quantity:1 slot single mounting facilityFeatures Provided:Holding spurMaterial:Stainless steelSurface Treatment:PassivateStyle Designator:	
120.0 Angle Between Mounting Facility And Loop Hinge Centerlines In Deg: 210.0 Accommodated Item Securing Device Type: Clamp Electron Tube Base Accommodated Diameter: +1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provided: Holding spur Material: Stainless steel Stainless steel Surface Treatment: Passivate Style Designator:	
Angle Between Mounting Facility And Loop Hinge Centerlines In Deg:210.0Accommodated Item Securing Device Type:ClampElectron Tube Base Accommodated Diameter:+1.337/+1.377 inchesMounting Facility Type And Quantity:1 slot single mounting facilityFeatures Provided:Holding spurStainless steelSurface Treatment:PassivateStyle Designator:	
210.0 Accommodated Item Securing Device Type: Clamp Electron Tube Base Accommodated Diameter: +1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provided: Holding spur Material: Stainless steel Stainless steel Surface Treatment: Passivate Style Designator:	
Accommodated Item Securing Device Type: Clamp Electron Tube Base Accommodated Diameter: +1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provided: Holding spur Holding spur Stainless steel Stainless steel Surface Treatment: Passivate Style Designator:	
Clamp Electron Tube Base Accommodated Diameter: +1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provided: Holding spur Holding spur Stainless steel Striace Treatment: Passivate Style Designator:	
Electron Tube Base Accommodated Diameter: +1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provided: Features Provided: Holding spur Holding spur Stainless steel Stainless steel Surface Treatment: Passivate Style Designator:	
+1.337/+1.377 inches Mounting Facility Type And Quantity: 1 slot single mounting facility Features Provided: Holding spur Holding spur Stainless steel Surface Treatment: Passivate Style Designator:	
Mounting Facility Type And Quantity:1 slot single mounting facilityFeatures Provided:Holding spurMaterial:Stainless steelSurface Treatment:PassivateStyle Designator:	
1 slot single mounting facility Features Provided: Holding spur Material: Stainless steel Surface Treatment: Passivate Style Designator:	
Features Provided: Holding spur Material: Stainless steel Surface Treatment: Passivate Style Designator:	
Holding spur Material: Stainless steel Surface Treatment: Passivate Style Designator:	
Material: Stainless steel Surface Treatment: Passivate Style Designator:	
Stainless steel Surface Treatment: Passivate Style Designator:	
Surface Treatment: Passivate Style Designator:	
Passivate Style Designator:	
Style Designator:	
Single foot, clip locked, tension clamp	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A062a0	