Diode Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-044-6652

Incloure Material: Glass Overall Length: 0.300 inches Terminal Length: 0.104 inches Punction For Which Designed: Zener diode Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 9.0 regulator voltage Voltage Tolerance In Percent: -5.0 to 5.0 Current Rating Per Characteristic: 50.0 n milliamperes voltage regulator diode current Power Rating Per Characteristic: 50.0 on milliamperes voltage regulator diode current Power Rating Per Characteristic: 50.0 n milliamperes voltage regulator diode current Power Rating Per Characteristic: 50.0 n milliamperes voltage regulator diode current Power Rating Per Characteristic: 50.0 n milliamperes voltage regulator diode current Power Rating Per Characteristic: 50.0 n milliamperes voltage regulator diode current Power Rating Per Characteristic: 50.0 n milliamperes voltage regulator diode current Power Rating Per Characteristic: 50.0 n milliamperes voltage regulator diode current Power Rating Per Characteristic: 50.0 n milliamperes voltage regulator diode current Power Rating Per Characteristic: 50.0 n milliamperes voltage regulator diode current Power Rating Per Characteristic: 50.0 n milliamperes voltage regulator diode current Power Rating Per Characteristic: 50.0 n milliamperes voltage regulator diode current Power Rating Per Characteristic: 50.0 n milliamperes voltage regulator diode current Power Rating Per Characteristic: 50.0 n milliamperes voltage Fig: Atitoad	
Overall Length:0.300 inchesTerminal Length:1.000 inchesOverall Diameter:0.104 inchesFunction For Which Designed:Zener diodeMounting Methode:TerminalFeatures Provided:Hermetically sealed caseSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:9.0 regulator voltageVoltage Tolerance In Percent:-5.0 no f.0Gurrent Rating Per Characteristic:7.50 milliamperes voltage regulator diode currentPower Rating Per Characteristic:7.50 no millivatts total device dissipationMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 unisulated wire leadSheft Hite:NaLui Of Measure:Femilitarization:NoFig:	
0.300 inches Terminal Length: 1.000 inches Overall Diameter: 0.104 inches Duction For Which Designed: 2 Ener diode Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 9.0 regulator voltage Voltage Tolerance In Percent: -5.0 to 5.0 Current Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Characteristic: 7.50 milliampters voltage regulator diode current Power Rating Per Power Rating Per Power Rating Per Power Ra	
Terminal Length:         1.000 inches         Overall Diameter:         0.104 inches         Function For Which Designed:         Zener diode         Mounting Method:         Terminal         Features Provided:         Hermetically sealed case         Semiconductor Material:         Silicon         Voltage Rating In Volts Per Characteristic:         9.0 regulator voltage         Voltage Tolerance In Percent:         -5.0 to 5.0         Current Rating Per Characteristic:         9.0.0 milliwatts total device dissipation         Maximum Operating Tempurature Per Measurement Point:         17.50 milliamperes voltage regulator diode current         Power Rating Per Characteristic:         9.0.0 angilliwatts total device dissipation         Maximum Operating Tempurature Per Measurement Point:         17.60 degrees celsius ambient air         Terminal Type And Quantily:         12 uninsulated wire lead         Shelf Life:         Na         Current Cating:         Int Of Measure:         Image:         Vatage State:         State:         If in the subsci Image:	
1.000 inches Vorall Diameter: Otorall Diameter: Otorall Diameter: Otoral Diameter: Otoral Diameter: Otoral Diameter: Caneer diode Function For Which Designed: Caneer diode Mounting Method: Terminal Features Provided: Featu	
Overall Diameter:0.104 inchesFunction For Which Designed:Zener diodeMounting Method:TerminalFeatures Provided:Hermetically sealed caseSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:9.0 regulator voltageVoltage Tolerance In Percent:-5.0 to 5.0Current Rating Per Characteristic:9.00. milliwatts total device dissipationMaximum Operating Tempurature Per Measurement Point:17.5.0 degrees celsius ambient airTerminal Type And Quantiy:2 unisulated wire leadSheff Life:N/aN/aFomiliarization:NoFig:	
0.104 inches         Function For Which Designed:         Zener diode         Mounting Method:         Terminal         Features Provided:         Hermetically sealed case         Semiconductor Material:         Silicon         Voltage Rating In Volts Per Characteristic:         9.0 regulator voltage         Voltage Tolerance In Percent:         -5.0 to 5.0         Current Rating Per Characteristic:         7.50 milliamperes voltage regulator diode current         Power Rating Per Characteristic:         7.50.0 milliwatts total device dissipation         Maximum Operating Tempurature Per Measurement Point:         175.0 degrees celsius ambient air         Terminal Type And Quantity:         2 uninsulated wire lead         Shelf Life:         Na         Pomiliarization:         r-         Fomiliarization:         No         Fig:	
Function For Which Designed:         Zener diode         Mounting Method:         Terminal         Features Provided:         Hermetically sealed case         Semiconductor Material:         Silicon         Votage Rating In Volts Per Characteristic:         9.0 regulator voltage         Votage Tolerance In Percent:         -5.0 to 5.0         Current Rating Per Characteristic:         9.00. milliamperes voltage regulator diode current         Power Rating Per Characteristic:         9.00. milliamperes voltage regulator diode current         Power Rating Per Characteristic:         9.00. milliamperes voltage regulator diode current         Power Rating Per Characteristic:         9.00. milliwatts total device dissipation         Maximum Operating Tempurature Per Measurement Point:         175.0 degrees celsius ambient air         Terminal Type And Quantity:         12 uninsulated wire lead         Shelf Life:         Na         Lint Of Measure:         -         Pomilitarization:         No         Fig:	
Zener diode  Mounting Method:  Terminal  Features Provided: Hermetically sealed case  Semiconductor Material: Solicon  Voltage Rating In Volts Per Characteristic: 9.0 regulator voltage  Voltage Tolerance In Percent: -5.0 to 5.0  Current Rating Per Characteristic: 7.50 milliamperes voltage regulator diode current Power Rating Per Characteristic: 500.0 milliwatts total device dissipation  Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Lift of Measure: - To Demilitarization: No	
Hounting Method:         Terminal         Features Provided:         Hermetically sealed case         Semiconductor Material:         Solicon         Voltage Rating In Volts Per Characteristic:         9.0 regulator voltage         Voltage Tolerance In Percent:         -5.0 to 5.0         Current Rating Per Characteristic:         7.50 milliamperes voltage regulator diode current         Power Rating Per Characteristic:         7.50 milliamperes voltage regulator diode current         Power Rating Per Characteristic:         7.50 milliamperes voltage regulator diode current         Power Rating Per Characteristic:         7.50 milliamperes voltage regulator diode current         Power Rating Per Characteristic:         7.50 milliamperes voltage regulator diode current         Power Rating Per Characteristic:         175.0 degrees celsius ambient air         Parminal Type And Quantity:         2 uninsulated wire lead         Shelf Life:         Ivid Measure:	
Terminal         Features Provided:         Hermetically sealed case         Semiconductor Material:         Silicon         Voltage Rating In Volts Per Characteristic:         9.0 regulator voltage         Voltage Tolerance In Percent:         -5.0 to 5.0         Current Rating Per Characteristic:         7.50 milliamperes voltage regulator diode current         Power Rating Per Characteristic:         50.0 milliwatts total device dissipation         Maximum Operating Tempurature Per Measurement Point:         175.0 degrees celsius ambient air         Terminal Type And Quantity:         2 uninsulated wire lead         Sheff Life:         N/a         Int of Measure:         -         Femilitarization:         No         Fig:	
Features Provided:         Hermetically sealed case         Semiconductor Material:         Solicon         Voltage Rating In Volts Per Characteristic:         9.0 regulator voltage         Voltage Tolerance In Percent:         -5.0 to 5.0         Current Rating Per Characteristic:         7.50 milliamperes voltage regulator diode current         Power Rating Per Characteristic:         50.0 milliwatts total device dissipation         Maximum Operating Tempurature Per Measurement Point:         175.0 degrees celsius ambient air         Terminal Type And Quantity:         2 uninsulated wire lead         Shelf Life:         N/a         Inf of Measure:            Pomiltarization:         Formiltarization:	
Hermetically sealed case         Semiconductor Material:         Solicon         Voltage Rating In Volts Per Characteristic:         9.0 regulator voltage         Voltage Tolerance In Percent:         -5.0 to 5.0         Current Rating Per Characteristic:         7.50 milliamperes voltage regulator diode current         Power Rating Per Characteristic:         50.0 milliwatts total device dissipation         Maximum Operating Tempurature Per Measurement Point:         175.0 degrees celsius ambient air         Terminal Type And Quantity:         2 uninsulated wire lead         Shelf Life:         Iv/a         Init Of Measure:         Imiliarization:         No         Fig:	
Semiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:9.0 regulator voltageVoltage Tolerance In Percent:-5.0 to 5.0Current Rating Per Characteristic:7.50 milliamperes voltage regulator diode currentPower Rating Per Characteristic:500.0 milliwatts total device dissipationMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aInit Of Measure:NoFig:	
Silicon Voltage Rating In Volts Per Characteristic: 9.0 regulator voltage Voltage Tolerance In Percent: -5.0 to 5.0 Current Rating Per Characteristic: 7.50 milliamperes voltage regulator diode current Power Rating Per Characteristic: 500.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Voltage Rating In Volts Per Characteristic:9.0regulator voltageVoltage Tolerance In Percent:-5.0 to 5.0Current Rating Per Characteristic:7.50 milliamperes voltage regulator diode currentPower Rating Per Characteristic:500.0 milliwatts total device dissipationMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aInit Of Measure:Demilitarization:NoFig:	
9.0 regulator voltage Voltage Tolerance In Percent: -5.0 to 5.0 Current Rating Per Characteristic: 7.50 milliamperes voltage regulator diode current Power Rating Per Characteristic: 500.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	
Voltage Tolerance In Percent:-5.0 to 5.0Current Rating Per Characteristic:7.50 milliamperes voltage regulator diode currentPower Rating Per Characteristic:500.0 milliwatts total device dissipationMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aUnit Of Measure:-NoFig:	
-5.0 to 5.0 Current Rating Per Characteristic: 7.50 milliamperes voltage regulator diode current Power Rating Per Characteristic: 500.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	
Current Rating Per Characteristic:7.50 milliamperes voltage regulator diode currentPower Rating Per Characteristic:500.0 milliwatts total device dissipationMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aUnit Of Measure:-Demilitarization:NoFig:	
7.50 milliamperes voltage regulator diode current Power Rating Per Characteristic: 500.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	
Power Rating Per Characteristic:500.0 milliwatts total device dissipationMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	
500.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	
Maximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	
175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	
Terminal Type And Quantity:   2 uninsulated wire lead   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:	
2 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	
Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fiig:	
N/a Unit Of Measure:  Demilitarization: No Fiig:	
Unit Of Measure:  Demilitarization: No Fiig:	
 Demilitarization: No Fiig:	
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	
A110a0	
	A110a0