Diode Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-058-8559

Inclosure Material: Glass Overall Length: 0.438 inches Terminal Length: 1.020 inches Overall Diameter: 0.160 inches Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage Current Rating Per Characteristic: 20.00 milliamperes reverse surge current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Overall Length:0.438 inchesTerminal Length:1.020 inchesOverall Diameter:0.160 inchesMounting Method:TerminalSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:8.2 regulator voltageCurrent Rating Per Characteristic:20.00 milliamperes reverse surge currentPower Rating Per Characteristic:1.0 watts small-signal input power, common-collector presetMaximum Operating Tempurature Per Measurement Point:150.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aUnit Of Measure:Demilitarization:No	Inclosure Material:
0.438 inches Terminal Length: 1.020 inches Overall Diameter: 0.160 inches Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage Current Rating Per Characteristic: 20.00 milliamperes reverse surge current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Glass
Terminal Length:1.020 inchesOverall Diameter:0.160 inchesMounting Method:TerminalSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:8.2 regulator voltageCurrent Rating Per Characteristic:20.00 milliamperes reverse surge currentPower Rating Per Characteristic:1.0 watts small-signal input power, common-collector presetMaximum Operating Tempurature Per Measurement Point:150.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aUnit Of Measure:-Demilitarization:No	Overall Length:
1.020 inches Overall Diameter: 0.160 inches Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage Current Rating Per Characteristic: 20.00 milliamperes reverse surge current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization:	0.438 inches
Overall Diameter:0.160 inchesMounting Method:TerminalSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:8.2 regulator voltageCurrent Rating Per Characteristic:20.00 milliamperes reverse surge currentPower Rating Per Characteristic:1.0 watts small-signal input power, common-collector presetMaximum Operating Tempurature Per Measurement Point:150.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aUnit Of Measure:Demilitarization:No	Terminal Length:
0.160 inches Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage Current Rating Per Characteristic: 20.00 milliamperes reverse surge current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	1.020 inches
Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage Current Rating Per Characteristic: 20.00 milliamperes reverse surge current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Overall Diameter:
Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage Current Rating Per Characteristic: 20.00 milliamperes reverse surge current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.160 inches
Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage Current Rating Per Characteristic: 20.00 milliamperes reverse surge current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Mounting Method:
Silicon Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage Current Rating Per Characteristic: 20.00 milliamperes reverse surge current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Terminal
Voltage Rating In Volts Per Characteristic: 8.2 regulator voltage Current Rating Per Characteristic: 20.00 milliamperes reverse surge current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Semiconductor Material:
 8.2 regulator voltage Current Rating Per Characteristic: 20.00 milliamperes reverse surge current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No 	Silicon
Current Rating Per Characteristic: 20.00 milliamperes reverse surge current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Voltage Rating In Volts Per Characteristic:
20.00 milliamperes reverse surge current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	8.2 regulator voltage
Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Current Rating Per Characteristic:
1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	20.00 milliamperes reverse surge current
Maximum Operating Tempurature Per Measurement Point: 150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Power Rating Per Characteristic:
150.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	1.0 watts small-signal input power, common-collector preset
Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Maximum Operating Tempurature Per Measurement Point:
2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	150.0 degrees celsius ambient air
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No	2 uninsulated wire lead
Unit Of Measure: Demilitarization: No	Shelf Life:
 Demilitarization: No	N/a
Demilitarization: No	Unit Of Measure:
No	
	Demilitarization:
Fiig:	No
	Fiig:
A110a0	A110a0