Thyristor Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-179-0698

| View Online at https://aerobasegroup.com/nsn/5961-00-179-0698     |   |
|---|---|
| Inclosure Material:   |   |
| Metal   |   |
| Overall Length:   |   |
| 0.673 inches  |   |
| Mounting Facility Quantity:                                       |   |
| 1   |   |
| Internal Configuration:   |   |
| Junction contact  |   |
| Electrode Internally-electrically Connected To Case:              |   |
| Collector   |   |
| Mounting Method:  |   |
| Threaded stud   |   |
| Features Provided:  |   |
| Hermetically sealed case  |   |
| Overall Width Across Flats:                                       |   |
| Between 0.551 inches and 0.557 inches                             |   |
| Thread Size:  |   |
| 0.250 inches  |   |
| Semiconductor Material:   |   |
| Silicon   |   |
| Voltage Rating In Volts Per Characteristic:                       |   |
| 600.0 breakover voltage, dc                                       |   |
| Current Rating Per Characteristic:                                |   |
| 35.00 amperes source cutoff current of standard range             |   |
| Power Rating Per Characteristic:                                  |   |
| 500.0 milliwatts small-signal input power, common-collector prese | t |
| Maximum Operating Tempurature Per Measurement Point:              |   |
| 100.0 degrees celsius case  |   |
| Special Features:   |   |
| Junction pattern arrangement: pnpn                                |   |
| Thread Series Designator:   |   |
|   |   |
| Terminal Type And Quantity:                                       |   |
| 1 threaded stud and 2 tab, solder lug                             |   |
| Shelf Life:   |   |
|   |   |
| Unit Of Measure:  |   |
| <br>Demilitarization:   |   |
| No  |   |
|   |   |
| Fiig:<br>A110a0   |   |
| ATTUdU  |   |