NSN 5961-00-232-3406

81349-mil-prf-19500/313 government specification

Shelf Life:

Transistor - Page 1 of 2

Inclosure Material:

Metal



View Online at https://aerobasegroup.com/nsn/5961-00-232-3406

| Overall Length: |
|--|
| 0.210 inches |
| Terminal Length: |
| 0.500 inches |
| Overall Diameter: |
| 0.230 inches |
| Internal Configuration: |
| Junction contact |
| Joint Electronic Device Engineering Council/jedec/case Outline Designation: |
| To-18 |
| Electrode Internally-electrically Connected To Case: |
| Collector |
| Mounting Method: |
| Terminal |
| Terminal Circle Diameter: |
| 0.100 inches |
| Features Provided: |
| Hermetically sealed case |
| Semiconductor Material: |
| Silicon |
| Voltage Rating In Volts Per Characteristic: |
| 45.0 collector to base voltage/static/emitter open and 45.0 collector to emitter voltage/static/base open and 18.0 emitter to base voltage, |
| static, collector open |
| Current Rating Per Characteristic: |
| 100.00 milliamperes source cutoff current |
| Power Rating Per Characteristic: |
| 600.0 milliwatts small-signal input power, common-collector preset |
| Transfer Ratio: |
| 10.0 small-signal short-circuit forward current transfer ratio, common-emitter |
| Maximum Operating Tempurature Per Measurement Point: |
| 175.0 degrees celsius junction |
| Special Features: |
| Junction pattern arrangement: npn |
| Test Data Document: |
| 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 3 uninsulated wire lead |
| Specification Data: |

NSN 5961-00-232-3406

Transistor - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A110a0

Mil-std (military Standard):

Mil-prf-19500 spec.