

View Online at <https://aerobasegroup.com/nsn/5961-00-247-5921>

Inclosure Material:

Metal

Overall Length:

Between 0.240 inches and 0.260 inches

Terminal Length:

Between 1.500 inches and 1.750 inches

Overall Diameter:

Between 0.335 inches and 0.370 inches

End Application:

Ticonderoga class cg (47); kidd class ddg; los angeles class ssn (688); sonar sets, an/bqs-14a/15; spruance class dd (963); forrestal class cv; sturgeon class cv; sturgeon class ssn (637); countermeasure set, an/slq-32; submarine antenna; nimitz class cvn

Internal Configuration:

Junction contact

Electrode Internally-electrically Connected To Case:

Collector

Mounting Method:

Terminal

Terminal Circle Diameter:

0.200 inches

Features Provided:

Hermetically sealed case

Criticality Code Justification:

Feat

Semiconductor Material:

Silicon

Voltage Rating In Volts Per Characteristic:

75.0 collector to base voltage/static/emitter open and 40.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open

Current Rating Per Characteristic:

1.50 amperes source cutoff current

Power Rating Per Characteristic:

2.9 watts small-signal input power, common-collector preset

Maximum Operating Temperature Per Measurement Point:

200.0 degrees celsius ambient air

Special Features:

Junction pattern arrangement: npn; weapon system essential

Test Data Document:

81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 uninsulated wire lead

Specification Data:

81349-mil-s-19500/395 government specification

Shelf Life:

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A110a0