NSN 5961-00-333-9077

Diode Semiconductor Device - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5961-00-333-9077 |
|--|
| Inclosure Material: |
| Glass |
| Overall Length: |
| Between 0.150 inches and 0.300 inches |
| Terminal Length: |
| Between 1.000 inches and 1.500 inches |
| Overall Diameter: |
| Between 0.115 inches and 0.155 inches |
| End Application: |
| Support equipment, b-1 aircraft; sonar signal processing sys, an/sqq-2 (v); helicopter, search and rescue, hh-60h; sonar acoustic |
| miscellaneous; ticonderoga class cg (47); telephone circuit switch, an/ttc-39; missile, all-weather antiship, harpoon (agm-84); close in |
| weapon system (ciws-phalanx); helicopter, carrier based asw, sh-60f; los angeles class ssn(688) |
| Mounting Method: |
| Terminal |
| Features Provided: |
| Hermetically sealed case |
| Criticality Code Justification: |
| Feat |
| Semiconductor Material: |
| Silicon |
| Voltage Rating In Volts Per Characteristic: |
| 400.0 working peak reverse voltage, peak total value |
| Current Rating Per Characteristic: |
| 80.00 amperes forward current, average preset |
| Maximum Operating Tempurature Per Measurement Point: |
| 175.0 degrees celsius ambient air |
| Special Features: |
| Weapon system essential |
| Test Data Document: |
| 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Specification Data: |
| 81349-mil-s-19500/424 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Fiig: A110a0

No