Diode Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-359-7588

| | sure Material: |
|--------|---|
| Glass | |
| | all Length: |
| | inches |
| | inal Length: |
| | inches |
| | all Diameter: |
| | inches |
| | tion For Which Designed: |
| | diode |
| Joint | Electronic Device Engineering Council/jedec/case Outline Designation: |
| Do-20 | 14ah |
| Moun | ting Method: |
| Termi | nal |
| Featu | res Provided: |
| Herm | etically sealed case |
| Semi | conductor Material: |
| Silico | n |
| Volta | ge Rating In Volts Per Characteristic: |
| 43.0 | regulator voltage |
| Volta | ge Tolerance In Percent: |
| -5.0/+ | 5.0 |
| Curre | ent Rating Per Characteristic: |
| 3.00 r | nilliamperes all primaries horsepower metric |
| Powe | r Rating Per Characteristic: |
| 500.0 | milliwatts small-signal input power, common-collector absolute |
| Maxir | num Operating Tempurature Per Measurement Point: |
| 200.0 | degrees celsius ambient air |
| Termi | inal Type And Quantity: |
| 2 unin | sulated wire lead |
| Speci | ification Data: |
| 80131 | -release5566 professional/industrial association specification |
| Shelf | Life: |
| N/a | |
| Unit C | Df Measure: |
| | |
| Demi | litarization: |
| No | |
| Fiig: | |
| - | aO |