Diode Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-411-2014

Metal Schware N198 inches and 0.371 inches Edware 0.1391 inches 1.000 inches Verall Edmate: Schware 0.128 inches and 0.285 inches Edware 0.128 inches and 0.285 inches Feature Provide:	losure Material:	
Beween 0.195 hohes and 0.371 inches Fremis Langui: 1.000 inches Overall Dameer: Beween 0.215 inches and 0.265 inches Electrode Internally-lectrically Connected To Case: Cathode Cathode Fouring Method: Cathode Fouring Method: Cathode Fouring Vorded Case Cathode Cat	al	
Terminal Length: 1.000 Inchesis Overal Diameter: Between 0.216 Inches and 0.265 Inches Electrode Internally-electrically Connected To Case: Cathods Bounding Method: Terminal Features Provided: Features Provided: Bounding Method: Semiconductor Material: Silcon Votage Rating In Vots Per Characteristic: 16.0 regulator votage Votage Rating In Vots Per Characteristic: 15.0 regulator votage Votage Rating Per Characteristic: 16.0 regulator votage Votage Rating Per Characteristic: 17.0 dage accelaus ambient air Test Data Document: 18.0 regulator votage 19.0 regulator votage requirements and test conditions that are apublications, reflecting general type data on certain 17.0 dage accelaus ambient air 18.0 and performance requirements and test conditions that are apublications, reflecting general type data on certain 19.0 regulator votage 19.0 regulator votage <	erall Length:	
1.000 index Overall Diameter: Between 0.216 inches and 0.266 inches Electrode Internally-electrically Connected To Case: Cathode Mounting Method: Terminal Petures Provided: Herretically sealed case Somiconductor Material: Silicon Vottage Tolerance In Percent: 5.0 //5.0 Current Rating Per Characteristic: 1.6.0 miguator voltage Vottage Tolerance In Percent: 5.0 //5.0 Current Rating Per Characteristic: 1.5.0 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.5.0 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.5.0 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.5.0 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.5.0 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.5.0 milliamperes all primaries horsepower common-collector preset Maximum Operating Tompurature Per Measurement Point: 15.0 doggee Calcula and int and test conditios that are shown as "typical", "acti	ween 0.195 inches and 0.371 inches	
Overall Diameter: Between 0.215 inches and 0.265 inches Electode Internally-electrically Connected To Case: Cathode Mounting Method:: Cathode Terminal Features Provided: Hemetically seade case Semiconductor Material: Silicon Voltage Tolerance In Percent: 5.0 regulation voltage Voltage Tolerance In Percent: 5.0 voltage Per Characteristic: 1.0 voltage Per Characteristic: 1.0 voltage methods in shorsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.0 voltas small-signali mott prover, common-collector preset Maximum Operating Tompurature Per Measurement Point: 1.75. o degrees cellus ambient air Test Data Document: 1.0 wata small-signali mott includus engimeening type bulletins, brochures, etc., that reflex specification specification requirements and test conditions that are shown as "typical", "average", ", etc.): Terminal Type And Quantity: 1.0 wata sellus ambient air 1.0 wata sellus and bertormace requirements and test conditions that are shown as "typical", "average", ", etc.): 1.0 wata sellus duive lead 1.0 mottenesure:	minal Length:	
Between 0.215 inches and 0.285 inches Ectrode Internally-electrically Connected To Case: Cathode Mounting Method: Terminal Features Provided: Features Provided: Bernelically sealed case Somiconductor Material: Solicon Voltage Rating In Volts Per Characteristic: 16.0 regulator voltage Voltage Tolerance In Percent: 50x 600 Current Rating Per Characteristic: 15.0 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 10 watts small-signal input power, common-collector preset Maximum Operating Tompurature Per Measurement Point: 175.0 degrees celsius ambient air Power Rating Per Characteristic: 10 watts small-signal input power, common-collector preset Maximum Operating Tompurature Per Measurement Point: 175.0 degrees celsius ambient air Power Rating Per Characteristic: 10 watts realed Specification (includes engineering type bulletins, brochures, etc., that reflect specification hype data on certain revicules commercial catalogs, industry directories, and similar trade publications, reflecting general type d	00 inches	
Electode Internally-electrically Connected To Case: Cathode Cathode Cathode Mounting Method: I reminal Features Provided: Features Provided: Features Provided: Hernetically sealed case Semiconductor Material: Silicon Voltage Characteristic: 16.0 regular voltage Voltage Tolerance In Percent: -5.045.0 Current Rating Per Characteristic: 15.0 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Pewer Rating Per Characteristic: 10.0 utats small-signal input power, common-collector preset Maximu Operating Tompurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 21.494-mil-pri-19500 specification (includes engineering type bulletins, brochuras, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type Ad Quantity: 21.41.42 Sindef Measure: 21	erall Diameter:	
Cabode Ca	ween 0.215 inches and 0.265 inches	
Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 16.0 regulator voltage Voltage Tolerance In Percent: -5.04-5.0 Current Rating Per Characteristic: 15.50 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 15.050 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 15.050 milliams small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 15.0 degrees celsius ambient air Test Data Document: 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 81349-mil-prf-19500/115 government specification Shelf Lite: Na Mi Mi Mi Lite: Na Lito I Measure: - - Demiliarization: Na Lito I Measure: - Demiliarization: Na Lito J Measure: - Lito J Mi Lito J Measure: - Lito J Mi Lito J Measure: - - - - - - - - - - - - -	ctrode Internally-electrically Connected To Case:	
Terminal sealed case sealed ca	hode	
Features Provided: Hermetically sealed case Semiconductor Material: Solicon Voltage Rating In Volts Per Characteristic: 16.0 regulator voltage Voltage Operance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 15.50 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 15.00 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 10.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Perto Ebaracce Inspecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification tormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performancer requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 2 unisulated wire lead Specification Data: 1349-mil-pri-19500/115 government specification Shef Life: Volt Geasure: Comilemization:	unting Method:	
Hemetically sealed case Semiconductor Material: Solicon Voltage Rating In Volts Per Characteristic: Solicon Voltage Rating In Volts Per Characteristic: Solve5:0 Voltage Tolerance In Percent:	minal	
Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 16.0 regulator voltage Voltage Tolerance In Percent: 5.0/45.0 Current Rating Per Characteristic: 15.50 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 10.0 watts small-signal input power, common-collector preset Waximu Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 13494-mil-pr19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain anvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 13494-mil-pr1-19500/115 government specification Sheft Life: Va Unit Of Measure: - Demiliarization: No Fig: 141040 Wil-set (military Standard):	itures Provided:	
Silicon Voltage Rating In Volts Per Characteristic: 16.0 regulator voltage Voltage Tolerance In Percent: 5.0/+5.0 Current Rating Per Characteristic: 15.50 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 10.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 131349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain anvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 81349-mil-prf-19500/115 government specification Sheft Life: Va Unit Of Measure:	metically sealed case	
Voltage Rating In Volts Per Characteristic: I6.0 regulator voltage Voltage Tolerance In Percent: 5.0/45.0 Surrent Rating Per Characteristic: 15.50 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 10. watts small-signal input power, common-collector preset Waximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 174.0 degrees celsius ambient air Test Data Document: 174.9 degrees celsius, industry directories, and similar trade publications, reflecting general type data in specification commat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain anvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 31349-mil-prf-19500/115 government specification Sheff Life: Va Jult Of Measure: - Demilitarization: No Sheff Life: Va Jult Jof Measure: - Demilitarization: No No No No No No No No No No	niconductor Material:	
 16.0 regulator voltage Voltage Tolerance In Percent: 5.0/45.0 Current Rating Per Characteristic: 15.50 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.0 watis small-signal input power, common-collector preset Waximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Fest Data Document: 1349-mil-pf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Ferminal Type And Quantity: 2 uninsulated wire lead Specification Data: 1349-mil-pf-19500/115 government specification Shelf Life: Va Jnit Of Measure: - 	con	
Voltage Tolerance In Percent: 45.0/45.0 Current Rating Per Characteristic: 15.50 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current. Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: B1349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: B1349-mil-prf-19500/115 government specification Shef Life: Va Unit Of Measure: 	tage Rating In Volts Per Characteristic:	
5.0 ⁴ 5.0 Current Rating Per Characteristic: 15.50 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 175.0 degrees celsius ambient air Test Data Document: 174.9 mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain anvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 31349-mil-prf-19500/115 government specification Sheff Life: Va Unit Of Measure: - - Demilitarization: No Flig: Al10a0 Wi-std (millitary Standard):	C regulator voltage	
Current Rating Per Characteristic: 15.50 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 81349-mil-pf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 81349-mil-pf-19500/115 government specification Sheff Life: Na Unit Of Measure: 	tage Tolerance In Percent:	
Ansatz and a set of the set of th	//+5.0	
Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain anvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 81349-mil-prf-19500/115 government specification Shelf Life: Va Unit Of Measure: Demilitarization: No Fig: A110a0	rrent Rating Per Characteristic:	
I. 0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 31349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain anvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 31349-mil-prf-19500/115 government specification Shelf Life: V/a Unit Of Measure: - Demilitarization: No Fiig: At10a0 Wil-std (military Standard):	50 milliamperes all primaries horsepower metric and 60.00 milliamperes repetitive peak forward current	
Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 31349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification iormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 31349-mil-prf-19500/115 government specification Shelf Life: V/a Unit Of Measure: - Demilitarization: No Filg: At10a0 Wi-std (military Standard):	ver Rating Per Characteristic:	
75.0 degrees celsius ambient air Fest Data Document: 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain servironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Ferminal Type And Quantity: 2 uninsulated wire lead Specification Data: 81349-mil-prf-19500/115 government specification Shelf Life: V/a Jnit Of Measure: - Demilitarization: No Filig: At10a0 Mil-setd (military Standard):	watts small-signal input power, common-collector preset	
Test Data Document: 31349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 20 uninsulated wire lead Specification Data: 31349-mil-prf-19500/115 government specification Shelf Life: V/a Juit Of Measure: - Demilitarization: No Fig: Alt0a0 Wil-std (military Standard):	ximum Operating Tempurature Per Measurement Point:	
Bar Sade Sade Sade Sade Sade Sade Sade Sade	0.0 degrees celsius ambient air	
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 31349-mil-prf-19500/115 government specification Shelf Life: V/a Unit Of Measure: Demilitarization: No Fiig: A110a0 Wil-std (military Standard):	at Data Document:	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 81349-mil-prf-19500/115 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A110a0 Mil-std (military Standard):	49-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type dat	ta in specification
Ferminal Type And Quantity: 2 uninsulated wire lead Specification Data: 31349-mil-prf-19500/115 government specification Shelf Life: \/a Jnit Of Measure: - Demilitarization: No Filg: A110a0 Wil-std (military Standard):	nat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data	on certain
e uninsulated wire lead Specification Data: 3/349-mil-prf-19500/115 government specification Shelf Life: 4/a Jnit Of Measure: - Demilitarization: No Sig: Alloa0 Mil-std (military Standard):	ironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Specification Data: B1349-mil-prf-19500/115 government specification Shelf Life: V/a Jnit Of Measure: - Demilitarization: No Fig: A110a0 Wil-std (military Standard):	minal Type And Quantity:	
Al 349-mil-prf-19500/115 government specification Shelf Life: V/a Jnit Of Measure: - Demilitarization: No Filg: Al 10a0 Wil-std (military Standard):	ninsulated wire lead	
Shelf Life: V/a Jnit Of Measure: - Demilitarization: No Fig: A110a0 Mil-std (military Standard):	ecification Data:	
V/a Unit Of Measure: Demilitarization: No Fiig: A110a0 Mil-std (military Standard):	49-mil-prf-19500/115 government specification	
Unit Of Measure: Demilitarization: No Fiig: A110a0 Mil-std (military Standard):	əlf Life:	
 Demilitarization: No Fiig: A110a0 Mil-std (military Standard):		
Demilitarization: No Fiig: A110a0 Mil-std (military Standard):	t Of Measure:	
No Fiig: A110a0 Mil-std (military Standard):		
Fiig: A110a0 Mil-std (military Standard):	nilitarization:	
A110a0 Mil-std (military Standard):		
Mil-std (military Standard):	ı:	
	0a0	
Mil-prf-19500 spec.	-std (military Standard):	
	prf-19500 spec.	