NSN 5961-00-411-7614

Thyristor Semiconductor Device - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5961-00-411-7614 |
|---|
| Inclosure Material: |
| Metal |
| Overall Length: |
| 0.420 inches |
| Terminal Length: |
| 0.375 inches |
| Overall Diameter: |
| 0.761 inches |
| Internal Configuration: |
| Junction contact |
| Mounting Method: |
| Terminal |
| Terminal Circle Diameter: |
| 0.130 inches |
| Features Provided: |
| Hermetically sealed case |
| Semiconductor Material: |
| |
| Silicon |
| Silicon Voltage Rating In Volts Per Characteristic: |
| |
| Voltage Rating In Volts Per Characteristic: |
| Voltage Rating In Volts Per Characteristic: 200.0 reverse voltage, peak |
| Voltage Rating In Volts Per Characteristic: 200.0 reverse voltage, peak Current Rating Per Characteristic: |
| Voltage Rating In Volts Per Characteristic: 200.0 reverse voltage, peak Current Rating Per Characteristic: 10.00 amperes forward current, average absolute |
| Voltage Rating In Volts Per Characteristic: 200.0 reverse voltage, peak Current Rating Per Characteristic: 10.00 amperes forward current, average absolute Terminal Type And Quantity: |
| Voltage Rating In Volts Per Characteristic: 200.0 reverse voltage, peak Current Rating Per Characteristic: 10.00 amperes forward current, average absolute Terminal Type And Quantity: 4 tab, solder lug |
| Voltage Rating In Volts Per Characteristic: 200.0 reverse voltage, peak Current Rating Per Characteristic: 10.00 amperes forward current, average absolute Terminal Type And Quantity: 4 tab, solder lug Specification Data: |
| Voltage Rating In Volts Per Characteristic: 200.0 reverse voltage, peak Current Rating Per Characteristic: 10.00 amperes forward current, average absolute Terminal Type And Quantity: 4 tab, solder lug Specification Data: 80131-release4707 professional/industrial association specification |
| Voltage Rating In Volts Per Characteristic: 200.0 reverse voltage, peak Current Rating Per Characteristic: 10.00 amperes forward current, average absolute Terminal Type And Quantity: 4 tab, solder lug Specification Data: 80131-release4707 professional/industrial association specification Shelf Life: |
| Voltage Rating In Volts Per Characteristic: 200.0 reverse voltage, peak Current Rating Per Characteristic: 10.00 amperes forward current, average absolute Terminal Type And Quantity: 4 tab, solder lug Specification Data: 80131-release4707 professional/industrial association specification Shelf Life: N/a |
| Voltage Rating In Volts Per Characteristic: 200.0 reverse voltage, peak Current Rating Per Characteristic: 10.00 amperes forward current, average absolute Terminal Type And Quantity: 4 tab, solder lug Specification Data: 80131-release4707 professional/industrial association specification Shelf Life: N/a |
| Voltage Rating In Volts Per Characteristic: 200.0 reverse voltage, peak Current Rating Per Characteristic: 10.00 amperes forward current, average absolute Terminal Type And Quantity: 4 tab, solder lug Specification Data: 80131-release4707 professional/industrial association specification Shelf Life: N/a Unit Of Measure: |
| Voltage Rating In Volts Per Characteristic: 200.0 reverse voltage, peak Current Rating Per Characteristic: 10.00 amperes forward current, average absolute Terminal Type And Quantity: 4 tab, solder lug Specification Data: 80131-release4707 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: |