NSN 5961-00-420-3668

Transistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5961-00-420-3668 |
|--|
| Inclosure Material: |
| Metal |
| Overall Length: |
| Between 0.170 inches and 0.210 inches |
| Terminal Length: |
| Between 0.500 inches and 0.750 inches |
| Overall Diameter: |
| Between 0.209 inches and 0.230 inches |
| Internal Configuration: |
| Junction contact |
| Electrode Internally-electrically Connected To Case: |
| Collector |
| Mounting Method: |
| Terminal |
| Terminal Circle Diameter: |
| 0.100 inches |
| Features Provided: |
| Hermetically sealed case |
| Semiconductor Material: |
| Silicon |
| Voltage Rating In Volts Per Characteristic: |
| 40.0 collector to base voltage/static/emitter open and 15.0 collector to emitter voltage/static/base open and 40.0 collector to emitter |
| voltage, dc with base short-circuited to emitter and 4.5 emitter to base voltage, static, collector open |
| Current Rating Per Characteristic: |
| 0.40 microamperes zero-gate-voltage source current outside diameter |
| Power Rating Per Characteristic: |
| 1.2 watts small-signal input power, common-collector preset |
| Maximum Operating Tempurature Per Measurement Point: |
| 200.0 degrees celsius junction |
| Special Features: |
| Junction pattern arrangement: npn |
| Test Data Document: |
| 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 3 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

NSN 5961-00-420-3668

Transistor - Page 2 of 2



Mil-std (military Standard):

Mil-prf-19500 spec.