## NSN 5961-00-422-5261

Transistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5961-00-422-5261



#### **Inclosure Material:**

Metal

## **Overall Length:**

Between 0.065 inches and 0.085 inches

## **Terminal Length:**

Between 0.500 inches and 0.750 inches

#### **Overall Diameter:**

Between 0.209 inches and 0.230 inches

#### **Internal Configuration:**

Junction contact

## Electrode Internally-electrically Connected To Case:

Collector

**Mounting Method:** 

Terminal

**Terminal Circle Diameter:** 

0.100 inches

#### **Features Provided:**

Hermetically sealed case

#### **Semiconductor Material:**

Silicon

## Voltage Rating In Volts Per Characteristic:

-60.0 collector to base voltage/static/emitter open and -60.0 collector to emitter voltage/static/base open and -5.0 emitter to base voltage, static, collector open

#### **Current Rating Per Characteristic:**

600.00 milliamperes source cutoff current

#### **Power Rating Per Characteristic:**

2.0 watts small-signal input power, common-collector preset

## Maximum Operating Tempurature Per Measurement Point:

200.0 degrees celsius ambient air

#### **Special Features:**

Junction pattern arrangement: pnp

## **Test Data Document:**

81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

3 uninsulated wire lead

#### **Specification Data:**

81349-mil-prf-19500/392 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

- **Demilitarization:**

# NSN 5961-00-422-5261

Transistor - Page 2 of 2

**Fiig:** A110a0

Mil-std (military Standard):

Mil-prf-19500 spec.

