Diode Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-425-3530

Inclosure Material: Glass Overall Length: 0.265 inches Terminal Length: 1.250 inches Overall Diameter: 0.096 inches Function For Which Designed: Current regulator Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-204aa Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Sheft Life: Na Unit Of Measure: Demilitarization: No	
Overall Length: 0.265 inches Terminal Length: 1.250 inches Overall Diameter: 0.096 inches Function For Which Designed: Current regulator Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-204aa Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 30131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Inclosure Material:
0.265 inchesFerninal Length:1.250 inchesOverall Diameter:0.096 inchesFunction For Which Designed:Current regulatorJoint Electronic Device Engineering Council/jedec/case Outline Designation:Do-204aaMounting Method:TerminalFeatures Provided:Hermetically sealed caseSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:100.0 forward voltage, averageCurrent Rating Per Characteristic:300.00 microamperes forward current, average peakPower Rating Per Characteristic:20.03 unisulated wire leadSpecification Data:80131-release5515 professional/industrial association specificationShelf Life:N/aUnit Of Measure:Init Of Measure:NoFig:	
Ferminal Length:1.250 inchesOverall Diameter:0.096 inchesFunction For Which Designed:Current regulatorJoint Electronic Device Engineering Council/jedec/case Outline Designation:Do-204aaMounting Method:TerminalFeatures Provided:Hermetically sealed caseSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:100.0 forward voltage, averageCurrent Rating Per Characteristic:30.00 microamperes forward current, average peakPower Rating Per Characteristic:10.01 direitanistical input power, common-collector absoluteFerminal Type And Quantity:2 uninsulated wire leadSpecification Data:Nol131-release5515 professional/industrial association specificationHerfNaInit Of Measure:NoFig:NoFig:	
1.250 inches Overall Diameter: 0.096 inches Function For Which Designed: Current regulator Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-204aa Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 30.00 microamperes forward current, average peak Power Rating Per Characteristic: 30.01 microamperes forward current, average peak Power Rating Per Characteristic: 30.01 microamperes forsward current, average peak Power Rating Per Characteristic: 3.01 misulated wire lead Specification Data: 80131 release5515 professional/industrial association specification Sheff Life: N/a Unit of Measure: - Demilitarization: No	
Overall Diameter: 0.096 inches Function For Which Designed: Current regulator Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-204aa Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 301.01 release5515 professional/industrial association specification Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig:	-
0.096 inches Function For Which Designed: Current regulator Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-204aa Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 forward voltage, average Current Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristic: 100.01 microamperes forward current, average peak Power Rating Per Characteristicurrent peak Power Rating Per Characteristic: 10	
Function For Which Designed: Current regulator Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-204aa Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Current regulator Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-204aa Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 2 uninsulated wire lead Specification Data: No Inter Characteristic: N/a Inter Characteristic: Inter Characterist	
Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-204aa Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: No Pomilitarization: No	
Do-204aa Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-
Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Terminal Features Provided: Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: N/a Unit Of Measure: T Demilitarization: No Fig:	
Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	-
Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Sheff Life: N/a Unit Of Measure: Demilitarization: No	Features Provided:
Silicon Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Hermetically sealed case
Voltage Rating In Volts Per Characteristic: 100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Semiconductor Material:
100.0 forward voltage, average Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Silicon
Current Rating Per Characteristic: 300.00 microamperes forward current, average peak Power Rating Per Characteristic: 6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Voltage Rating In Volts Per Characteristic:
300.00 microamperes forward current, average peak Power Rating Per Characteristic: 6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	100.0 forward voltage, average
Power Rating Per Characteristic: 6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Current Rating Per Characteristic:
6.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	300.00 microamperes forward current, average peak
Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Rating Per Characteristic:
2 uninsulated wire lead Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	6.0 watts small-signal input power, common-collector absolute
Specification Data: 80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
80131-release5515 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	2 uninsulated wire lead
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	80131-release5515 professional/industrial association specification
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A110a0	Fiig:
	A110a0