Diode Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-480-6895

Meal Overlaitungth: Corrental Length: 1000 Inches Overlait Dimeter: Between 0.215 Inches and 0.265 Inches Elected Internally-electrically Connected To Case: Cathole Moniting Method: Terminal Petters Provided: Patters Provided: Petters Provided: <	osure Material:	
9.571 inches 1.000 inches 0.000 inches 0.000 inches Between 0.215 inches and 0.285 inches Electrode internally-decirically Connected To Case: Cathode Cathode Notating Method: Terminal Femetically sealed case Semonductor Material: Solo Voltage Tolerance In Percent: 20.7 regulator voltage Voltage Tolerance In Percent: 20.7 orgulator voltage Voltage Tolerance In Percent: 10.7 orgulator percentere 20.7 orgulator voltage Voltage Tolerance Intervetere 21.7 orgulator voltage 21.7 orgulator voltage <td>al</td> <td></td>	al	
Terminal Length: 1.000 Inches Overall Diameter: Educend Dicholes and 0.265 inches Electrode Internally-electrically Connected To Case: Cathods Mounting Method: Terminal Features Provided: Features Provided: Remetically sealed case Semiconductor Material: Solicon Voltage Rating In Volts Per Characteristic: Solicon Voltage Orderance In Percent: Solor Voltage Orderance In Percent: Solor Voltage Orderance In Percent: Solor Voltage Orderance Information Envolumemention and 11.00 milliamperes repetitive paek forward current Power Rating Per Characteristic: Now Rating Per Characteristic: No wort Rating Per Characteristic: Voltage Calculation (includes engineering type bulletins, brochures, etc., that reflect specification type data on carinal Voltage Soles andipering House specifications, industry directories, and similar trade publications, reflecting general type data on carinal Voltage Calculation (includes engineering type bulletins, brochures, etc., that reflect specification type data on carinal Voltage Calculation (includes engineering type bullet	rall Length:	
1.000 Indees Overall Diametes: Batwane 0.216 inches and 0.266 inches Electode Internally-electically Connected To Case: Cathode Moniting Method: Terminal Features Provided: Features Provided: Votage Atting In Votts Per Characteristic: 201 regulator votage Votage Tolerance In Percent: 20 votage Tolerance In Percent: 20 votage Tolerance In Percent: 10 votatis mall-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient ait Toreinal Type And Quantity: valuades durine lead 10 watis mall-signal input power, common-collector preset Brace Tole Comment: 12.0 degree Celsius ambient ait 12.0 degree Celsius ambient ait 13.0 degree Celsius ambient specification 14.1 degree Characteristic: 12.0 degree Celsius ambient specificatin functious design	1 inches	
Overall Diameter: Botween 0.215 inches an 0.265 inches Electrode Internally-electrically Connected To Case: Cathode Stanting Method: Terminal Features Provided: Hormsteinity sealed case Stantion Station Station Station Station Provides Station Provides Station Provides Station Provides Station Station Provides Provides Station Provides Station Provides Station Station Station Station Provides Station St	ninal Length:	
Between 0.215 inches and 0.265 inches Electrode Internally-electrically Connected To Case: Cathode Hounting Method: Terminal Features Provided: Features Provided: Beamcing State Case Somiconductor Material: Solicon Voltage Rating In Volts Per Characteristic: 82.0 regulator voltage Voltage Tolerance In Persont: 50.45.0 Our methad per Characteristic: 8.00 milliamperes all primaries horsepower metric and 11.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 10 vants mail-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 110 vants mail-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 120 values commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain revironmental and performance requirements and test conditions that are shown as 'typical'', 'average'', ', etc.): Termina Type And Quantity: 2 values dive lead Specification format peeclification Specification Specification (andust peeclification spresenting the publications, reflecting gene	0 inches	
Electrode Internally-electrically Connected To Case: Cathode Mounting Method: Terminal Features Provided: Patures provided: Mountiquity Sealed case Semiconductor Material: Silicon Voltage Rall In Volts Per Characteristic: S2:0 regulator voltage Voltage Tolerance In Percent: S0:0 regulator voltage Voltage Tolerance In Percent: S0:0 regulator voltage Voltage Tolerance In Percent: S0:0 regulator percent: <tr< td=""><td>rall Diameter:</td><td></td></tr<>	rall Diameter:	
Cabode Ca	veen 0.215 inches and 0.265 inches	
Mounting Method: Terminal Fractures Provided: Features Provided: Barmendialy sealed case Semiconductor Material: Solicon Voltage Rating In Volts Per Characteristic: Solicon Voltage Rating In Volts Per Characteristic: Solicon Voltage Tolerance In Percent: Soloco Current Rating Per Characteristic: Soloco Soloco Soloco Soloco Power Rating Per Characteristic: Soloco Solo milliamperes all primaries horsepower metric and 11.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: Soloco Solo degrees celsius ambient air Soloco Power Rating Per Characteristic: Soloco Solo degrees celsius ambient air Soloco Power Rating Per Characteristic: Soloco Soloco Soloco Soloco Soloco Soloco Soloco Soloco Soloco	trode Internally-electrically Connected To Case:	
Terminal sealed case sealed ca	node	
Features Provided: Hermetically sealed case Semiconductor Material: Solicon Voltage Rating In Volts Per Characteristic: 20. regulator voltage Voltage Tolerance In Percent: -5.0v+5.0 Current Rating Per Characteristic: 3.00 milliamperes all primaries horsepower metric and 11.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 81349-mil-pr1-91500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 81349-mil-pr1-19500 speciment specification Shoft Life: No Nation B1349-mil-pr1-19500115 government specification Shoft Life: No Entitie: No Entitie: No <t< td=""><td>Inting Method:</td><td></td></t<>	Inting Method:	
Hemetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: Silicon Voltage Rating In Volts Per Characteristic: Silicon Voltage Rolerance In Percent:	ninal	
Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 32.0 regulator voltage Voltage Tolerance In Percent: 5.0/45.0 Current Rating Per Characteristic: 3.00 milliamperes all primaries horsepower metric and 11.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximu Operating Tempurature Per Measurement Point: 1.75.0 degrees celsius ambient air Test Data Document: 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain anvironmental and performance requirements and test conditions that are shown as "typical", "average", "*, etc.). Terminal Type And Quantity: 21 uninsulated wire lead Specification Data: 81349-mil-prf-19500/115 government specification 81494-mil-prf-19500/115 government specification 81404-mil-prf-19500/115 government specification 81404-mil-prf-19500/115 government specification 81404-mil-prf-19500/115 government specification 81404-mil-prf-19500/115 government specification 81404-mil-prf-19500/115 government specification 81404-mil-prf-19500/115 go	tures Provided:	
Silion Votage Rating In Votts Per Characteristic: 82.0 regulator votage Votage Tolerance In Percent: 45.0/45.0 Current Rating Per Characteristic: 8.0 on milliamperes all primaries horsepower metric and 11.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 10 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air 175.0 degrees celsius celsius ambient air 175.0 degrees celsius ambient air 175.0 de	netically sealed case	
Voltage Rating In Volts Per Characteristic: 32.0 regulator voltage Voltage Tolerance In Percent: 5.0/45.0 Current Rating Per Characteristic: 3.00 milliamperes all primaries horsepower metric and 11.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 175.0 degrees celsius ambient air Test Data Document: 174.9 mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 81349-mil-prf-19500/115 government specification Sheff Life: Va Unit Of Measure: - - Domilitarization: No Fig: Atitoa0 Mil-set (military Standard):	niconductor Material:	
82.0 regulator voltage Voltage Tolerance In Percent: -5.0/45.0 Current Rating Per Characteristic: 3.00 milliamperes all primaries horsepower metric and 11.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.00 williamperes all primaries horsepower metric and 11.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.0 withs small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 1 B1349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Terminal Type And Quantity: 2 unisulated wire lead Specification Data: B1349-mil-prf-19500/115 government specification Shelf Life: Na Unit Of Measure: - Domilitarization: No Flig: A110a0 Mil-estd (milltary Standard):	on	
Voltage Tolerance In Percent: 5.0/+5.0 Current Rating Per Characteristic: 3.00 milliamperes all primaries horsepower metric and 11.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 31349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification anvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 31349-mil-prf-19500/115 government specification Sheff Life: Va Unit Of Measure: - - Demilitarization: No Filg: AltoaO Mil-std (military Standard):	age Rating In Volts Per Characteristic:	
5.5/45.0 Current Rating Per Characteristic: 3.00 milliamperes all primaries horsepower metric and 11.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 81349-mil-prf-19500/115 government specification Shelf Life: Na Unit Of Measure:	regulator voltage	
Current Rating Per Characteristic: 3.00 milliamperes all primaries horsepower metric and 11.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 81349-mil-pf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 81349-mil-pf-19500/115 government specification Sheft Life: N/a Unit Of Measure:	age Tolerance In Percent:	
Aloo milliamperes all primaries horsepower metric and 11.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 31349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Terminal Type And Quanity: 2 uninsulated wire lead Specification Data: 31349-mil-prf-19500/115 government specification Sheff Life: Va Unit Of Measure:	/+5.0	
Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain anvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 81349-mil-prf-19500/115 government specification Shelf Life: Va Unit Of Measure: Demilitarization: No Fig: A110a0	rent Rating Per Characteristic:	
A lo watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Test Data Document: 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 81349-mil-prf-19500/115 government specification Shelf Life: V/a Unit Of Measure: Demilitarization: No Filg: A110a0 Wil-std (military Standard):	milliamperes all primaries horsepower metric and 11.00 milliamperes repetitive peak forward current	
Waximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Fest Data Document: 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 81349-mil-prf-19500/115 government specification Shelf Life: V/a Unit Of Measure: - - Demilitarization: No Filg: At10a0 Winstruk (military Standard):	ver Rating Per Characteristic:	
T75.0 degrees celsius ambient air Test Data Document: 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain anvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 81349-mil-prf-19500/115 government specification Shelf Life: V/a Jnit Of Measure: - Demilitarization: No Filig: At10a0 Mil-setd (military Standard):	watts small-signal input power, common-collector preset	
Test Data Document: B1349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: B1349-mil-prf-19500/115 government specification Shelf Life: V/a Demilitarization: No Filg: A10a0 Wil-std (military Standard):	imum Operating Tempurature Per Measurement Point:	
Alagemil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Ferminal Type And Quantity: 2 uninsulated wire lead Specification Data: 31349-mil-prf-19500/115 government specification Shelf Life: 4/a Jnit Of Measure: - Demilitarization: No Fig: Al10a0 Mil-std (military Standard):	0 degrees celsius ambient air	
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 31349-mil-prf-19500/115 government specification Shelf Life: v/a Jnit Of Measure: - Demilitarization: No Fiig: A110a0	t Data Document:	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 31349-mil-prf-19500/115 government specification Shelf Life: V/a Unit Of Measure: 	49-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in	specification
Ferminal Type And Quantity: 2: uninsulated wire lead Specification Data: 31349-mil-prf-19500/115 government specification Shelf Life: 4/a Jnit Of Measure: - Demilitarization: No Filg: A110a0 Mil-std (military Standard):	at; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on o	certain
2 uninsulated wire lead Specification Data: 3/349-mil-prf-19500/115 government specification Shelf Life: 4/a Jnit Of Measure: - Demilitarization: No Filg: A110a0 Mil-std (military Standard):	ronmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Specification Data: B1349-mil-prf-19500/115 government specification Shelf Life: V/a Jnit Of Measure: - Demilitarization: No Fig: A110a0 Mil-std (military Standard):	ninal Type And Quantity:	
Al 349-mil-prf-19500/115 government specification Shelf Life: V/a Jnit Of Measure: - Demilitarization: No Filg: Al 10a0 Mil-std (military Standard):	insulated wire lead	
Shelf Life: V/a Unit Of Measure: 	cification Data:	
V/a Jnit Of Measure: - - Demilitarization: No Fiig: A110a0 Mil-std (military Standard):	49-mil-prf-19500/115 government specification	
Unit Of Measure: Demilitarization: No Fiig: A110a0 Mil-std (military Standard):	If Life:	
 Demilitarization: No Fiig: A110a0 Mil-std (military Standard):		
Demilitarization: No Fiig: A110a0 Mil-std (military Standard):	COf Measure:	
No Fiig: A110a0 Mil-std (military Standard):		
Fiig: A110a0 Mil-std (military Standard):	nilitarization:	
A110a0 Mil-std (military Standard):		
Mil-std (military Standard):	:	
	0a0	
Mil-prf-19500 spec.	std (military Standard):	
	orf-19500 spec.	