Diode Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-481-4195

Slass Dverall Length: 	ering Council/jedec/case Outline Designation:
A 325 inches Ferminal Length: Between 1.000 inches and 1.625 inches Doverall Diameter: 0.225 inches Doint Electronic Device Engineering Council/jedec/case Outline Designation: Do-13 Mounting Method: Ferminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 70.1 reverse voltage, peak Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector absolute Ferminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release6049 professional/industrial association specification Shelf Life: Va Juit Of Measure: - Demilitarization: No	ering Council/jedec/case Outline Designation: macteristic: r, common-collector absolute
Between 1.000 inches and 1.625 inches Devrall Diameter: 0.225 inches Doint Electronic Device Engineering Council/jedec/case Outline Designation: Do-13 Mounting Method: Ferminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 70.1 reverse voltage, peak Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector absolute Ferminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: V/a Unit Of Measure: - Demilitarization: No	ering Council/jedec/case Outline Designation: macteristic: r, common-collector absolute
Between 1.000 inches and 1.625 inches Devrall Diameter: 0.225 inches Doint Electronic Device Engineering Council/jedec/case Outline Designation: Do-13 Mounting Method: Ferminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 70.1 reverse voltage, peak Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector absolute Ferminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: V/a Unit Of Measure: - Demilitarization: No	ering Council/jedec/case Outline Designation: macteristic: r, common-collector absolute
2.225 inches Joint Electronic Device Engineering Council/jedec/case Outline Designation: Jo-13 Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 70.1 reverse voltage, peak Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector absolute Ferminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: Va Jnit Of Measure: - Demilitarization: No	aracteristic: c: r, common-collector absolute
Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-13 Wounting Method: Ferminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 70.1 reverse voltage, peak Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector absolute Ferminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Sheff Life: Va Jnit Of Measure: - Demilitarization:	aracteristic: c: r, common-collector absolute
Do-13 Mounting Method: Ferminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 70.1 reverse voltage, peak Power Rating Per Characteristic: 70.1 reverse voltage, peak Power Rating Per Characteristic: 70.1 unissulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: Va Juit Of Measure: - Demilitarization: No	aracteristic: c: r, common-collector absolute
Mounting Method: Terminal Features Provided: termetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 70.1 reverse voltage, peak Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: Va Jnit Of Measure: - Demilitarization: No	c: r, common-collector absolute
Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 70.1 reverse voltage, peak Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector absolute Ferminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: V/a Jnit Of Measure: - Demilitarization: No	c: r, common-collector absolute
Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 70.1 reverse voltage, peak Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: V/a Juit Of Measure: - - Demilitarization:	c: r, common-collector absolute
Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 70.1 reverse voltage, peak Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector absolute Ferminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: V/a Junit Of Measure: - No	c: r, common-collector absolute
Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 70.1 reverse voltage, peak Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: V/a Unit Of Measure: - Demilitarization: No	c: r, common-collector absolute
Silicon Voltage Rating In Volts Per Characteristic: 70.1 reverse voltage, peak Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: V/a Jnit Of Measure: - Demilitarization: No	c: r, common-collector absolute
Voltage Rating In Volts Per Characteristic: 70.1 reverse voltage, peak Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: V/a Jnit Of Measure: - Demilitarization: No	c: r, common-collector absolute
70.1 reverse voltage, peak Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: V/a Jnit Of Measure: - Demilitarization: No	c: r, common-collector absolute
Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: V/a Jnit Of Measure: - Demilitarization: No	r, common-collector absolute
1.0 watts small-signal input power, common-collector absolute Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: V/a Jnit Of Measure: - Demilitarization: No	r, common-collector absolute
Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: V/a Jnit Of Measure: - Demilitarization: No	
2 uninsulated wire lead Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: V/a Jnit Of Measure: Demilitarization: No	ndustrial association specification
Specification Data: 30131-release6049 professional/industrial association specification Shelf Life: V/a Jnit Of Measure: - Demilitarization:	ndustrial association specification
30131-release6049 professional/industrial association specification Shelf Life: V/a Jnit Of Measure: - Demilitarization: No	ndustrial association specification
Shelf Life: V/a Jnit Of Measure: Demilitarization: No	ndustrial association specification
∿/a Jnit Of Measure: Demilitarization: No	
Jnit Of Measure: Demilitarization: No	
 Demilitarization: No	
Demilitarization:	
No	
Filg:	