

View Online at https://aerobasegroup.com/nsn/5961-00-572-7435

2.250 inches Overall Height: 1.000 inches Overall Width: 0.750 inches Circuit Connection Style Designator: Bridge 3 phase Absolute Maximum Voltage Rating In Volts Per Characteristic: 600.0 peak inverse voltage Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: 7 Erminal Material: Silicon Terminal Type And Quantity: 3 wire hook and 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	
Overall Height:1.000 inchesOverall Width:0.750 inchesCircuit Connection Style Designator:Bridge 3 phaseAbsolute Maximum Voltage Rating In Volts Per Characteristic:600.0 peak inverse voltageAbsolute Maximum Current Rating Per Characteristic:25.00 amperes average forward current averaged over a full 60-hz cycleMounting Method:TerminalMaterial:SiliconTerminal Type And Quantity:3 wire hook and 2 tab, solder lugShelf Life:N/aUnit Of Measure:Demilitarization:No	Overall Length:
1.000 inches Overall Width: 0.750 inches Circuit Connection Style Designator: Bridge 3 phase Absolute Maximum Voltage Rating In Volts Per Characteristic: 600.0 peak inverse voltage Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: 7 Erminal Material: Silicon Terminal Type And Quantity: 3 wire hook and 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	2.250 inches
Overall Width:0.750 inchesCircuit Connection Style Designator:Bridge 3 phaseAbsolute Maximum Voltage Rating In Volts Per Characteristic:600.0 peak inverse voltageAbsolute Maximum Current Rating Per Characteristic:25.00 amperes average forward current averaged over a full 60-hz cycleMounting Method:TerminalMaterial:SiliconTerminal Type And Quantity:3 wire hook and 2 tab, solder lugShelf Life:N/aUnit Of Measure:-Demilitarization:No	Overall Height:
0.750 inches Circuit Connection Style Designator: Bridge 3 phase Absolute Maximum Voltage Rating In Volts Per Characteristic: 600.0 peak inverse voltage Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: 7 erminal Material: Silicon Ferminal Type And Quantity: 3 wire hook and 2 tab, solder lug Shelf Life: N/a Init Of Measure: Demilitarization: No	1.000 inches
Circuit Connection Style Designator: Bridge 3 phase Absolute Maximum Voltage Rating In Volts Per Characteristic: 600.0 peak inverse voltage Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Terminal Material: Silicon Terminal Type And Quantity: 3 wire hook and 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Overall Width:
Bridge 3 phase Absolute Maximum Voltage Rating In Volts Per Characteristic: 600.0 peak inverse voltage Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Terminal Material: Silicon Terminal Type And Quantity: 3 wire hook and 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.750 inches
Absolute Maximum Voltage Rating In Volts Per Characteristic: 600.0 peak inverse voltage Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Terminal Material: Silicon Terminal Type And Quantity: 3 wire hook and 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Circuit Connection Style Designator:
600.0 peak inverse voltage Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Terminal Material: Silicon Terminal Type And Quantity: 3 wire hook and 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Bridge 3 phase
Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Terminal Material: Silicon Terminal Type And Quantity: 3 wire hook and 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Absolute Maximum Voltage Rating In Volts Per Characteristic:
25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Terminal Material: Silicon Terminal Type And Quantity: 3 wire hook and 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	600.0 peak inverse voltage
Mounting Method: Terminal Material: Silicon Terminal Type And Quantity: 3 wire hook and 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	Absolute Maximum Current Rating Per Characteristic:
Terminal Material: Silicon Terminal Type And Quantity: 3 wire hook and 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	25.00 amperes average forward current averaged over a full 60-hz cycle
Material: Silicon Terminal Type And Quantity: 3 wire hook and 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization:	Mounting Method:
Silicon Terminal Type And Quantity: 3 wire hook and 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	Terminal
Terminal Type And Quantity: 3 wire hook and 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	Material:
3 wire hook and 2 tab, solder lug Shelf Life: N/a Unit Of Measure: Demilitarization: No	Silicon
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No	3 wire hook and 2 tab, solder lug
Unit Of Measure: Demilitarization: No	Shelf Life:
 Demilitarization: No	N/a
Demilitarization: No	Unit Of Measure:
No	
	Demilitarization:
File	No
ing.	Fiig:

A503j0