Diode Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-574-3842

| Glass | S |
|--------|--|
| | all Length: |
| |) inches |
| | ninal Length: |
| | 5 inches |
| | all Diameter: |
| 0.145 | 5 inches |
| Func | ction For Which Designed: |
| | er diode |
| Mour | nting Method: |
| Term | inal |
| Featu | ures Provided: |
| Herm | netically sealed case |
| Semi | iconductor Material: |
| Silico | n |
| Volta | age Rating In Volts Per Characteristic: |
| 27.0 | regulator voltage |
| Volta | age Tolerance In Percent: |
| -5.0/+ | +5.0 |
| Curre | ent Rating Per Characteristic: |
| 50.00 | D milliamperes all primaries horsepower metric |
| Powe | er Rating Per Characteristic: |
| 5.0 w | atts small-signal input power, common-collector preset |
| Maxi | mum Operating Tempurature Per Measurement Point: |
| 175.0 | 0 degrees celsius ambient air |
| Term | ninal Type And Quantity: |
| 2 unii | nsulated wire lead |
| Shelf | f Life: |
| N/a | |
| Unit | Of Measure: |
| | |
| | ilitarization: |
| No | |
| Fiig: | |
| A110 | Da0 |