Thyristor Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-609-0494

| closure Material:   |         |
|---|---------|
| astic   |         |
| verall Length:  |         |
| 625 inches  |         |
| erminal Length:   |         |
| 562 inches  |         |
| verall Height:  |         |
| 190 inches  |         |
| verall Width:   |         |
| 420 inches  |         |
| ternal Configuration:   |         |
| unction contact   |         |
| pint Electronic Device Engineering Council/jedec/case Outline Desig | nation: |
| p-220ab   |         |
| ectrode Internally-electrically Connected To Case:                  |         |
| ollector  |         |
| ounting Method:   |         |
| erminal   |         |
| emiconductor Material:  |         |
| licon   |         |
| oltage Rating In Volts Per Characteristic:                          |         |
| 6 on-state voltage, peak  |         |
| urrent Rating Per Characteristic:                                   |         |
| 00 amperes forward current, total rms horsepower metric             |         |
| ower Rating Per Characteristic:                                     |         |
| 0.0 watts small-signal input power, common-collector blank          |         |
| aximum Operating Tempurature Per Measurement Point:                 |         |
| 25.0 degrees celsius junction                                       |         |
| pecial Features:  |         |
| Inction pattern arrangement: pnpn                                   |         |
| erminal Type And Quantity:  |         |
| pin   |         |
| helf Life:  |         |
| /a  |         |
| nit Of Measure:   |         |
|   |         |
| emilitarization:  |         |
| 0   |         |
| ig:   |         |
| 110a0   |         |