NSN 5961-00-838-4664

Transistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-838-4664

Inclosure Material:
Metal
Overall Length:
0.250 inches
Terminal Length:
1.500 inches
Overall Diameter:
0.359 inches
Internal Configuration:
Junction contact
Electrode Internally-electrically Connected To Case:
Collector
Mounting Method:
Terminal
Terminal Circle Diameter:
0.200 inches
Features Provided:
Hermetically sealed case
Semiconductor Material:
Silicon
Valtana Dating In Valta Day Obanastaniatias
Voltage Rating In Volts Per Characteristic:
for the set of the set
60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown
60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open
60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic:
 60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliwatts small-signal input power, common-collector
 60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic:
 60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliwatts small-signal input power, common-collector Special Features: Junction pattern arrangement: pnp
60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliwatts small-signal input power, common-collector Special Features: Junction pattern arrangement: pnp Terminal Type And Quantity:
 60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliwatts small-signal input power, common-collector Special Features: Junction pattern arrangement: pnp Terminal Type And Quantity: 3 uninsulated wire lead
 60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliwatts small-signal input power, common-collector Special Features: Junction pattern arrangement: pnp Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life:
60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliwatts small-signal input power, common-collector Special Features: Junction pattern arrangement: pnp Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a
 60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliwatts small-signal input power, common-collector Special Features: Junction pattern arrangement: pnp Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life:
60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliwatts small-signal input power, common-collector Special Features: Junction pattern arrangement: pnp Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliamperes cutoff cutoff cutoff cutoff cutoff cutoff cutoff cutoff cutof
60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliwatts small-signal input power, common-collector Special Features: Junction pattern arrangement: pnp Terminal Type And Quantity: 3 unisulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No
60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 600.0 milliampteres source cutoff current Power Rating Per Characteristic: 70 Pomillateristeristeristeristeristeristeristeris
60.0 breakdown voltage, collector-to-base, emitter open and 40.0 breakdown voltage, collector-to-emitter, base open and 5.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 600.0 milliwatts small-signal input power, common-collector Special Features: Junction pattern arrangement: pnp Terminal Type And Quantity: 3 unisulated wire lead Shelf Life: N/a Unit Of Measure: - - Demilitarization: No