NSN 5961-00-851-0178

Transistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-851-0178

View Online at https://aerobasegroup.com/nsn/5961-00-851-0178
Inclosure Material:
Metal
Overall Length:
0.250 inches
Terminal Length:
1.500 inches
Overall Diameter:
0.320 inches
Internal Configuration:
Junction contact
Electrode Internally-electrically Connected To Case:
Collector
Mounting Method:
Terminal
Terminal Circle Diameter:
0.200 inches
Features Provided:
Hermetically sealed case
Semiconductor Material:
Silicon
Voltage Rating In Volts Per Characteristic:
Voltage Rating In Volts Per Characteristic:
Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous
Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic:
 Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset
 Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset Power Rating Per Characteristic:
 Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector
 Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector Maximum Operating Tempurature Per Measurement Point:
 Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction
 Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features:
 Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn
 Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Terminal Type And Quantity:
 Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Terminal Type And Quantity: 3 uninsulated wire lead
 Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life:
 Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a
 Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a
 Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization:
 Voltage Rating In Volts Per Characteristic: 90.0 collector to emitter voltage, dc and 7.0 emitter to base voltage, instantaneous Current Rating Per Characteristic: 1.00 microamperes zero-gate-voltage source current preset Power Rating Per Characteristic: 1.0 watts small-signal input power, common-collector Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Terminal Type And Quantity: 3 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No