Diode Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-890-4742

Iclosure Material: Glass Overall Length: 0.500 inches Terminal Length: 1.250 inches Mounting Method: Terminal Terminal Circle Diameter: 0.030 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Sheff Life: N/a Unit Of Measure: - - Perilitarization: Yes - demil/mli	Glass Overall Length: 0.500 inches Terminal Length: 1.250 inches Mounting Method: 1.250 inches Mounting Method: Terminal Terminal Terminal Circle Diameter: 0.030 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Sheff Life: N/a Unit Of Measure: - Demilitarization: Yes - demil/mli		
Overal Length:0.500 inchesTerminal Length:1.250 inchesMounting Method:TerminalTerminal Circle Diameter:0.030 inchesFeatures Provided:Hermetically sealed caseSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:6.8 regulator voltageCurrent Rating Per Characteristic:7.50 milliamperes source cutoff current horsepower metricMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadSpecification Or Standard:1n2765 typeShelf Life:N/aUht Of Measure:-Demilitarization:Yes - demil/mil	ContentOverall Length:0.500 inchesTerminal Length:1.250 inchesMounting Method:TerminalTerminalCircle Diameter:0.030 inchesFeatures Provided:Hermetically sealed caseSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:6.8 regulator voltageCurrent Rating Per Characteristic:7.50 milliamperes source cutoff current horsepower metricMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadSpecification Or Standard:1n2765 typeShelf Life:N/aUnit Of Measure:-Demilitarization:Yes - demil/mliFig:	Inclosure Material:	
0.500 inchesTerminal Length:1.250 inchesMounting Method:TerminalTerminal Circle Diameter:0.030 inchesFeatures Provided:Hermetically sealed caseSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:6.8 regulator voltageCurrent Rating Per Characteristic:7.50 milliamperes source cutoff current horsepower metricMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadSpecification Or Standard:In2765 typeShelf Life:N/aUnit of Measure:Permilitarization:Yes - demil/mli	0.500 inchesTerminal Length:1.250 inchesMounting Method:TerminalTerminal Circle Diameter:0.030 inchesFeatures Provided:Hermetically sealed caseSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:6.8 regulator voltageCurrent Rating Per Characteristic:7.50 milliamperes source cutoff current horsepower metricMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadSpecification Or Standard:N/aUnit Of Measure:Penilitarization:Yes - demil/mliFig:	Glass	
Terminal Length: 1.250 inches 1.250 inches Mounting Method: Terminal Terminal Terminal Circle Diameter: 0.030 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Terminal Length: 1.250 inches Mounting Method: Terminal Terminal Terminal Terminal Terminal Terminal Circle Diameter: 0.030 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Overall Length:	
1.250 inches Mounting Method: Terminal Terminal Circle Diameter: 0.030 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit of Measure: - Permiltarization: Parameter Station: Parameter Station: Parameter Station: N/a Durit of Measure: - Permiltarization: Permiltarization:	1.250 inches Mounting Method: Terminal Terminal Terminal Circle Diameter: 0.030 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 75.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: - Demiliarization: Yes - demil/mli Fig:	0.500 inches	
Mounting Method: Terminal Terminal Circle Diameter: 0.030 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Mounting Method: Terminal Terminal Circle Diameter: 0.030 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: - Demiliarization: Yes - demil/mli Fig:	Terminal Length:	
Terminal Terminal Terminal Circle Diameter: Co30 inches Features Provided: Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: Co30 inches Current Rating Per Characteristic: Current Current Per Measurement Point: Current Rating Per Characteristic: Current Rating Per Characteristic: Current Rating Per Characteristic: Current Rating Per Characteristic: Curren	Terminal Terminal Terminal Circle Diameter: O.030 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: In2765 type Shelf Life: N/a Unit Of Measure: - Demilitarization: Yes - demil/mli Fig:	1.250 inches	
Terminal Circle Diameter:0.030 inchesFeatures Provided:Hermetically sealed caseSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:6.8 regulator voltageCurrent Rating Per Characteristic:7.50 milliamperes source cutoff current horsepower metricMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadSpecification Or Standard:1n2765 typeShelf Life:N/aUnit Of Measure:-Perintiarization:Yes - demil/mli	Terminal Circle Diameter:0.030 inchesFeatures Provided:Hermetically sealed caseSemiconductor Material:SoliconVoltage Rating In Volts Per Characteristic:6.8 regulator voltageCurrent Rating Per Characteristic:7.50 milliamperes source cutoff current horsepower metricMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadSpecification Or Standard:1n2765 typeShelf Life:N/aUnit Of Measure:-Penilitarization:Yes - demil/mliFig:	Mounting Method:	
0.030 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Pemilitarization: Yes - demil/mli	0.030 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Pemilitarization: Yes - demil/mli	Terminal	
Features Provided:Hermetically sealed caseSemiconductor Material:SoliconVoltage Rating In Volts Per Characteristic:6.8 regulator voltageCurrent Rating Per Characteristic:7.50 milliamperes source cutoff current horsepower metricMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadSpecification Or Standard:1n2765 typeShelf Life:N/aUnit Of Measure:Permiliarization:Yes - demil/mli	Features Provided:Hermetically sealed caseSemiconductor Material:SoliconVoltage Rating In Volts Per Characteristic:6.8 regulator voltageCurrent Rating Per Characteristic:7.50 milliamperes source cutoff current horsepower metricMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadSpecification Or Standard:1n2765 typeShelf Life:N/aUnit Of Measure:Femilitarization:Yes - demil/mliFig:	Terminal Circle Diam	leter:
Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 7.50 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Lint Of Measure: Demilitarization: Yes - demil/mli	Hermetically sealed caseSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:6.8 regulator voltageCurrent Rating Per Characteristic:7.50 milliamperes source cutoff current horsepower metricMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadSpecification Or Standard:1n2765 typeShelf Life:N/aUnit Of Measure:Femilitarization:Yes - demil/mliFig:	0.030 inches	
Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Life: N/a Lift Of Measure: Demilitarization: Yes - demil/mli	Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 7.50 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Sec	Features Provided:	
Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air 175.0 degrees celsius ambient air 175.0 degrees celsius ambient air 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Silicon Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 75.0 degrees celsius ambient air T5.0 degrees celsius ambient air T5.0 degrees celsius ambient air 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Fig:	Hermetically sealed ca	ase
Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Voltage Rating In Volts Per Characteristic: 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Semiconductor Mate	rial:
 6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: - Demilitarization: Yes - demil/mli 	6.8 regulator voltage Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	Silicon	
Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Current Rating Per Characteristic: 7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air 7erminal Type And Quantity: 2 uninsulated wire lead 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Mit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Voltage Rating In Vo	Its Per Characteristic:
7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	7.50 milliamperes source cutoff current horsepower metric Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	6.8 regulator voltage	
Maximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadSpecification Or Standard:1n2765 typeShelf Life:N/aUnit Of Measure:Pemilitarization:Yes - demil/mli	Maximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadSpecification Or Standard:1n2765 typeShelf Life:N/aUnit Of Measure:Pemilitarization:Yes - demil/mliFig:	Current Rating Per C	haracteristic:
175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fig:	7.50 milliamperes sou	rce cutoff current horsepower metric
Terminal Type And Quantity:2 uninsulated wire leadSpecification Or Standard:1n2765 typeShelf Life:N/aUnit Of Measure:Pemilitarization:Yes - demil/mli	Terminal Type And Quantity: 2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Maximum Operating	Tempurature Per Measurement Point:
2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	2 uninsulated wire lead Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	175.0 degrees celsius	ambient air
Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Specification Or Standard: 1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Terminal Type And G	luantity:
1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	1n2765 type Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	2 uninsulated wire lead	d
Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli	Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Specification Or Star	ndard:
N/a Unit Of Measure: Demilitarization: Yes - demil/mli	N/a Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	1n2765 type	
Unit Of Measure: Demilitarization: Yes - demil/mli	Unit Of Measure: Demilitarization: Yes - demil/mli Fiig:	Shelf Life:	
 Demilitarization: Yes - demil/mli	 Demilitarization: Yes - demil/mli Fiig:	N/a	
Yes - demil/mli	Yes - demil/mli Fiig:	Unit Of Measure:	
Yes - demil/mli	Yes - demil/mli Fiig:		
	Fiig:	Demilitarization:	
Fiig:	-	Yes - demil/mli	
	A110a0	Fiig:	
A110a0		A110a0	