

| <ul> <li>View Online at https://aerobasegroup.com/nsn/5961-00-892-9959</li> <li>Inclosure Material: Metal Overall Length: <ul> <li>0.180 inches</li> <li>Terminal Length:</li> <li>1.500 inches</li> </ul> </li> <li>Overall Diameter: <ul> <li>0.370 inches</li> </ul> </li> <li>Component Name And Quantity:</li> <li>2 transistor</li> <li>Mounting Method:</li> <li>Terminal</li> <li>Circle Diameter:</li> <li>0.200 inches</li> </ul> <li>Features Provided: <ul> <li>Hermetically sealed case</li> <li>Semiconductor Material:</li> <li>Silicon all transistor</li> <li>Voltage Rating In Volts Per Characteristic:</li> <li>60.00 milliamperes source cutoff current all transistor</li> <li>Power Rating Per Characteristic:</li> <li>2.0 milliwatts small-signal input power, common-collector absolute all transistor</li> </ul></li> |                  |
|--|------------------|
| Metal         Overall Length:         0.180 inches         Terminal Length:         1.500 inches         Overall Diameter:         0.370 inches         Component Name And Quantity:         2 transistor         Mounting Method:         Terminal         Circle Diameter:         0.200 inches         Features Provided:         Hermetically sealed case         Semiconductor Material:         Silicon all transistor         Votage Rating In Volts Per Characteristic:         600. collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper         Current Rating Per Characteristic:         600.00 milliamperes source cutoff current all transistor   |                  |
| Overall Length:         0.180 inches         Terminal Length:         1.500 inches         Overall Diameter:         0.370 inches         Component Name And Quantity:         2 transistor         Mounting Method:         Terminal         Terminal         Terminal         Terminal         Features Provided:         Hermetically sealed case         Semiconductor Material:         Silicon all transistor         Voltage Rating In Volts Per Characteristic:         60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper         Current Rating Per Characteristic:         600.00 milliamperes source cutoff current all transistor         Power Rating Per Characteristic:  |                  |
| 0.180 inchesTerminal Length:1.500 inchesOverall Diameter:0.370 inchesComponent Name And Quantity:2 transistorMounting Method:TerminalTerminal Circle Diameter:0.200 inchesFeatures Provided:Hermetically sealed caseSemiconductor Material:Silicon all transistorVoltage Rating In Volts Per Characteristic:60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter operCurrent Rating Per Characteristic:600.00 milliamperes source cutoff current all transistorPower Rating Per Characteristic:   |                  |
| Terminal Length:1.500 inchesOverall Diameter:0.370 inchesComponent Name And Quantity:2 transistorMounting Method:1 transiatorMounting Method:1 terminalCreminal Circle Diameter:0.200 inchesFeatures Provided:Hermetically sealed caseSemiconductor Material:Silicon all transistorVoltage Rating In Volts Per Characteristic:60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter operCurrent Rating Per Characteristic:600.00 milliamperes source cutoff current all transistorPower Rating Per Characteristic:   |                  |
| <ul> <li>1.500 inches</li> <li>Overall Diameter:</li> <li>0.370 inches</li> <li>Component Name And Quantity:</li> <li>2 transistor</li> <li>Mounting Method:</li> <li>Terminal</li> <li>Terminal Circle Diameter:</li> <li>0.200 inches</li> <li>Features Provided:</li> <li>Hermetically sealed case</li> <li>Semiconductor Material:</li> <li>Silicon all transistor</li> <li>Voltage Rating In Volts Per Characteristic:</li> <li>60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper</li> <li>Current Rating Per Characteristic:</li> <li>600.00 milliamperes source cutoff current all transistor</li> <li>Power Rating Per Characteristic:</li> </ul>   |                  |
| Overall Diameter:0.370 inchesComponent Name And Quantity:2 transistorMounting Method:TerminalTerminal Circle Diameter:0.200 inchesFeatures Provided:Hermetically sealed caseSemiconductor Material:Silicon all transistorVoltage Rating In Volts Per Characteristic:60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter operCurrent Rating Per Characteristic:600.00 milliamperes source cutoff current all transistorPower Rating Per Characteristic:   |                  |
| 0.370 inches<br>Component Name And Quantity:<br>2 transistor<br>Mounting Method:<br>Terminal<br>Terminal Circle Diameter:<br>0.200 inches<br>Features Provided:<br>Hermetically sealed case<br>Semiconductor Material:<br>Silicon all transistor<br>Voltage Rating In Volts Per Characteristic:<br>60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper<br>Current Rating Per Characteristic:<br>600.00 milliamperes source cutoff current all transistor<br>Power Rating Per Characteristic:  |                  |
| Component Name And Quantity:<br>2 transistor<br>Mounting Method:<br>Terminal<br>Terminal Circle Diameter:<br>0.200 inches<br>Features Provided:<br>Hermetically sealed case<br>Semiconductor Material:<br>Silicon all transistor<br>Voltage Rating In Volts Per Characteristic:<br>60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper<br>Current Rating Per Characteristic:<br>600.00 milliamperes source cutoff current all transistor<br>Power Rating Per Characteristic:  |                  |
| 2 transistor Mounting Method: Terminal Terminal Circle Diameter: 0.200 inches Features Provided: Hermetically sealed case Semiconductor Material: Silicon all transistor Voltage Rating In Volts Per Characteristic: 60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper Current Rating Per Characteristic: 600.00 milliamperes source cutoff current all transistor  |                  |
| Mounting Method:<br>Terminal<br>Terminal Circle Diameter:<br>0.200 inches<br>Features Provided:<br>Hermetically sealed case<br>Semiconductor Material:<br>Silicon all transistor<br>Voltage Rating In Volts Per Characteristic:<br>60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper<br>Current Rating Per Characteristic:<br>600.00 milliamperes source cutoff current all transistor<br>Power Rating Per Characteristic:  |                  |
| Terminal Circle Diameter:<br>0.200 inches<br>Features Provided:<br>Hermetically sealed case<br>Semiconductor Material:<br>Silicon all transistor<br>Voltage Rating In Volts Per Characteristic:<br>60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper<br>Current Rating Per Characteristic:<br>600.00 milliamperes source cutoff current all transistor  |                  |
| Terminal Circle Diameter:0.200 inchesFeatures Provided:Features Provided:Hermetically sealed caseSemiconductor Material:Silicon all transistorVoltage Rating In Volts Per Characteristic:60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter operCurrent Rating Per Characteristic:600.00 milliamperes source cutoff current all transistorPower Rating Per Characteristic:  |                  |
| 0.200 inches<br>Features Provided:<br>Hermetically sealed case<br>Semiconductor Material:<br>Silicon all transistor<br>Voltage Rating In Volts Per Characteristic:<br>60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper<br>Current Rating Per Characteristic:<br>600.00 milliamperes source cutoff current all transistor<br>Power Rating Per Characteristic:   |                  |
| Features Provided:         Hermetically sealed case         Semiconductor Material:         Silicon all transistor         Voltage Rating In Volts Per Characteristic:         60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper         Current Rating Per Characteristic:         600.00 milliamperes source cutoff current all transistor         Power Rating Per Characteristic:   |                  |
| Hermetically sealed case<br>Semiconductor Material:<br>Silicon all transistor<br>Voltage Rating In Volts Per Characteristic:<br>60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper<br>Current Rating Per Characteristic:<br>600.00 milliamperes source cutoff current all transistor<br>Power Rating Per Characteristic:   |                  |
| Semiconductor Material:<br>Silicon all transistor<br>Voltage Rating In Volts Per Characteristic:<br>60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper<br>Current Rating Per Characteristic:<br>600.00 milliamperes source cutoff current all transistor<br>Power Rating Per Characteristic:   |                  |
| Silicon all transistor<br>Voltage Rating In Volts Per Characteristic:<br>60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper<br>Current Rating Per Characteristic:<br>600.00 milliamperes source cutoff current all transistor<br>Power Rating Per Characteristic:  |                  |
| <ul> <li>Voltage Rating In Volts Per Characteristic:</li> <li>60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper</li> <li>Current Rating Per Characteristic:</li> <li>600.00 milliamperes source cutoff current all transistor</li> <li>Power Rating Per Characteristic:</li> </ul>  |                  |
| <ul> <li>60.0 collector to base voltage, dc all transistor and 30.0 collector to base voltage/static/emitter oper</li> <li><b>Current Rating Per Characteristic:</b></li> <li>600.00 milliamperes source cutoff current all transistor</li> <li><b>Power Rating Per Characteristic:</b></li> </ul>   |                  |
| Current Rating Per Characteristic:<br>600.00 milliamperes source cutoff current all transistor<br>Power Rating Per Characteristic:   |                  |
| 600.00 milliamperes source cutoff current all transistor Power Rating Per Characteristic:  | n all transistor |
| Power Rating Per Characteristic:   |                  |
| -  |                  |
| 2.0 milliwatts small-signal input power, common-collector absolute all transistor  |                  |
|  |                  |
| Maximum Operating Tempurature Per Measurement Point:   |                  |
| 200.0 degrees celsius junction   |                  |
| Special Features:  |                  |
| All transistor junction pattern arrangement: npn   |                  |
| Terminal Type And Quantity:  |                  |
| 6 uninsulated wire lead  |                  |
| Shelf Life:  |                  |
| N/a  |                  |
| Unit Of Measure:   |                  |
|  |                  |
| Demilitarization:  |                  |
| No   |                  |
| Fiig:  |                  |
| A110a0   |                  |