## NSN 5961-00-913-2893

Transistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-913-2893

View Online at https://aerobasegroup.com/nsn/5961-00-913-2893
Inclosure Material:
Metal
Overall Length:
0.210 inches
Terminal Length:
0.500 inches
Overall Diameter:
0.230 inches
Internal Configuration:
Junction contact
Electrode Internally-electrically Connected To Case:
Collector
Mounting Method:
Terminal
Terminal Circle Diameter:
0.100 inches
Features Provided:
Hermetically sealed case
Semiconductor Material:
Silicon
Voltage Rating In Volts Per Characteristic:
Voltage Rating In Volts Per Characteristic: 50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown
50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown
50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open
<ul> <li>50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open</li> <li>Current Rating Per Characteristic:</li> <li>600.00 milliamperes source cutoff current</li> <li>Power Rating Per Characteristic:</li> </ul>
<ul> <li>50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open</li> <li>Current Rating Per Characteristic:</li> <li>600.00 milliamperes source cutoff current</li> <li>Power Rating Per Characteristic:</li> <li>400.0 milliwatts small-signal input power, common-collector</li> </ul>
<ul> <li>50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open</li> <li>Current Rating Per Characteristic:</li> <li>600.00 milliamperes source cutoff current</li> <li>Power Rating Per Characteristic:</li> <li>400.0 milliwatts small-signal input power, common-collector</li> <li>Special Features:</li> </ul>
<ul> <li>50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open</li> <li>Current Rating Per Characteristic:</li> <li>600.00 milliamperes source cutoff current</li> <li>Power Rating Per Characteristic:</li> <li>400.0 milliwatts small-signal input power, common-collector</li> <li>Special Features:</li> <li>Junction pattern arrangement: pnp</li> </ul>
<ul> <li>50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open</li> <li>Current Rating Per Characteristic:</li> <li>600.00 milliamperes source cutoff current</li> <li>Power Rating Per Characteristic:</li> <li>400.0 milliwatts small-signal input power, common-collector</li> <li>Special Features:</li> <li>Junction pattern arrangement: pnp</li> <li>Terminal Type And Quantity:</li> </ul>
<ul> <li>50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open</li> <li>Current Rating Per Characteristic:</li> <li>600.00 milliamperes source cutoff current</li> <li>Power Rating Per Characteristic:</li> <li>400.0 milliwatts small-signal input power, common-collector</li> <li>Special Features:</li> <li>Junction pattern arrangement: pnp</li> <li>Terminal Type And Quantity:</li> <li>3 uninsulated wire lead</li> </ul>
<ul> <li>50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open</li> <li>Current Rating Per Characteristic:</li> <li>600.00 milliamperes source cutoff current</li> <li>Power Rating Per Characteristic:</li> <li>400.0 milliwatts small-signal input power, common-collector</li> <li>Special Features:</li> <li>Junction pattern arrangement: pnp</li> <li>Terminal Type And Quantity:</li> <li>3 uninsulated wire lead</li> <li>Specification Data:</li> </ul>
<ul> <li>50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open</li> <li>Current Rating Per Characteristic:</li> <li>600.00 milliamperes source cutoff current</li> <li>Power Rating Per Characteristic:</li> <li>400.0 milliwatts small-signal input power, common-collector</li> <li>Special Features:</li> <li>Junction pattern arrangement: pnp</li> <li>Terminal Type And Quantity:</li> <li>3 uninsulated wire lead</li> <li>Specification Data:</li> <li>80131-release4555 professional/industrial association specification</li> </ul>
<ul> <li>50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open</li> <li>Current Rating Per Characteristic:</li> <li>600.00 milliamperes source cutoff current</li> <li>Power Rating Per Characteristic:</li> <li>400.0 milliwatts small-signal input power, common-collector</li> <li>Special Features:</li> <li>Junction pattern arrangement: pnp</li> <li>Terminal Type And Quantity:</li> <li>3 uninsulated wire lead</li> <li>Specification Data:</li> <li>80131-release4555 professional/industrial association specification</li> </ul>
50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 400.0 milliwatts small-signal input power, common-collector Special Features: Junction pattern arrangement: pnp Terminal Type And Quantity: 3 unisulated wire lead Specification Data: 80131-release4555 professional/industrial association specification Shelf Life: N/a
<ul> <li>50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open</li> <li>Current Rating Per Characteristic:</li> <li>600.00 milliamperes source cutoff current</li> <li>Power Rating Per Characteristic:</li> <li>400.0 milliwatts small-signal input power, common-collector</li> <li>Special Features:</li> <li>Junction pattern arrangement: pnp</li> <li>Terminal Type And Quantity:</li> <li>3 uninsulated wire lead</li> <li>Specification Data:</li> <li>80131-release4555 professional/industrial association specification</li> </ul>
50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 400.0 milliwatts small-signal input power, common-collector Special Features: Junction pattern arrangement: pnp Terminal Type And Quantity: 3 uninsulated wire lead Specification Data: 80131-release4555 professional/industrial association specification Shelf Life: N/a Unit Of Measure:
50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 400.0 milliwatts small-signal input power, common-collector Special Features: Junction pattern arrangement: pnp Terminal Type And Quantity: 3 uninsulated wire lead Specification Data: N/a Unit of Measure: Demilitarization:
50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open         Current Rating Per Characteristic:         600.00 milliamperes source cutoff current         Power Rating Per Characteristic:         400.0 milliwatts small-signal input power, common-collector         Special Features:         Junction pattern arrangement: pnp         Terminal Type And Quantity:         3 uninsulated wire lead         Specification Data:         Roth Life:         N/a         Unit of Measure:         Imiliarization:         No
50.0 breakdown voltage, collector-to-base, emitter open and 35.0 breakdown voltage, collector-to-emitter, base open and 4.0 breakdown voltage, emitter-to-base, collector open Current Rating Per Characteristic: 600.00 milliamperes source cutoff current Power Rating Per Characteristic: 400.0 milliwatts small-signal input power, common-collector Special Features: Junction pattern arrangement: pnp Terminal Type And Quantity: 3 uninsulated wire lead Specification Data: N/a Unit of Measure: Demilitarization: