

View Online at <https://aerobasegroup.com/nsn/5961-00-931-7028>

Inclosure Material:

Metal

Overall Length:

Between 0.240 inches and 0.260 inches

Terminal Length:

Between 0.500 inches and 0.750 inches

Overall Diameter:

Between 0.335 inches and 0.370 inches

End Application:

Radar, series an/sps-4 (v); airborne mobile dir air spt ctl (21d), (02m jul 83) (an/uyq-3a); defense communications radio (9 systems); missile, air-to-air sparrow (aim-7); communications, lha; support equipment, b-52 aircraft; countermeasure set, an/slq-32; close in weapon system (ciws-phalanx); aircra ft, (ac-130h, mc-130h, ec-130e, hc-130)

Internal Configuration:

Junction contact

Electrode Internally-electrically Connected To Case:

Collector

Mounting Method:

Terminal

Terminal Circle Diameter:

0.200 inches

Features Provided:

Hermetically sealed case

Criticality Code Justification:

Feat

Semiconductor Material:

Silicon

Voltage Rating In Volts Per Characteristic:

60.0 collector to base voltage/static/emitter open and 30.0 collector to emitter voltage/static/base open and 3.5 emitter to base voltage, static, collector open

Current Rating Per Characteristic:

400.00 milliamperes source cutoff current

Power Rating Per Characteristic:

1.0 watts small-signal input power, common-collector preset

Maximum Operating Tempurature Per Measurement Point:

175.0 degrees celsius junction

Special Features:

Weapon system essential; junction pattern arrangement: npn

Test Data Document:

81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 uninsulated wire lead

Specification Data:

81349-mil-prf-19500/398 government specification

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A110a0

Mil-std (military Standard):

Mil-prf-19500 spec.