NSN 5961-00-950-6588

Diode Semiconductor Device - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5961-00-950-6588

View Online at https://aerobasegroup.com/nsn/5961-00-950-6588
Inclosure Material:
Metal
Overall Length:
1.253 inches
Mounting Facility Quantity:
1
Electrode Internally-electrically Connected To Case:
Cathode
Mounting Method:
Threaded stud
Features Provided:
Hermetically sealed case
Overall Width Across Flats:
Between 0.424 inches and 0.437 inches
Thread Size:
0.190 inches
Semiconductor Material:
Silicon
Voltage Rating In Volts Per Characteristic:
5.1 regulator voltage
Voltage Tolerance In Percent:
-5.0/+5.0
Current Rating Per Characteristic:
0.49 amperes all primaries horsepower metric and 1.84 amperes repetitive peak forward current
Power Rating Per Characteristic:
10.0 watts small-signal input power, common-collector preset
Maximum Operating Tempurature Per Measurement Point:
150.0 degrees celsius case
Precious Material:
Gold or silver
Test Data Document:
81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unf
Terminal Type And Quantity:
1 threaded stud and 1 tab, solder lug
Specification Data:
81349-mil-s-19500/272 government specification
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5961-00-950-6588

Diode Semiconductor Device - Page 2 of 2



Demi		

No

Fiig:

A110a0

Mil-std (military Standard):

Mil-prf-19500 spec.