Diode Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-962-0533

Overall Length:         0.405 inches         Overall Diameter:         0.424 inches         Mounting Facility Quantity:         1         Joint Electronic Device Engineering Council/jedec/case Outline Designation:         D0-4         Mounting Method:         Threaded stud         Features Provided:         Hermetically sealed case         Overall Width Across Flats:         Between 0.424 inches and 0.437 inches         Thread Size:         0.190 inches         Semiconductor Material:         Silicon         Voltage Rating In Volts Per Characteristic:         100.0 reverse voltage, peak         Current Rating Per Characteristic:         300.00 amperes forward current, average absolute         Maximum Operating Tempurature Per Measurement Point:         200.0 degrees celsius case         Thread Stud and 1 tab, solder lug         Specification Data:         80131-release3851 professional/industrial association specification         Sheft Life:         N/a         Unit Of Measure:	Inclosure Material:
0.405 inches Overall Diameter: 0.424 inches Mounting Facility Quantity: 1 Joint Electronic Device Engineering Council/jedec/case Outline Designation: D0-4 Mounting Method: Threaded stud Features Provided: Hermetically sealed case Overall Width Across Flats: Between 0.424 inches and 0.437 inches Thread Size: 0.190 inches Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Metal
Overall Diameter:         0.424 inches         Mounting Facility Quantity:         1         Joint Electronic Device Engineering Council/jedec/case Outline Designation:         D0-4         Mounting Method:         Threaded stud         Features Provided:         Hermetically sealed case         Overall Width Across Flats:         Between 0.424 inches and 0.437 inches         Thread Size:         0.190 inches         Semiconductor Material:         Silicon         Voltage Rating In Volts Per Characteristic:         100.0 reverse voltage, peak         Current Rating Per Characteristic:         300.00 amperes forward current, average absolute         Maximum Operating Tempurature Per Measurement Point:         200.0 degrees celsius case         Thread Stue and 1 tab, solder lug         Specification Data:         80131-release3851 professional/industrial association specification         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No	Overall Length:
0.424 inches Mounting Facility Quantity: 1 Joint Electronic Device Engineering Council/jedec/case Outline Designation: D0-4 Mounting Method: Threaded stud Features Provided: Hermetically sealed case Overall Width Across Flats: Between 0.424 inches and 0.437 inches Thread Size: 0.190 inches Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	0.405 inches
Mounting Facility Quantity: 1 Joint Electronic Device Engineering Council/jedec/case Outline Designation: D0-4 Mounting Method: Threaded stud Features Provided: Hermetically sealed case Overall Width Across Flats: Between 0.424 inches and 0.437 inches Thread Size: 0.190 inches Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Overall Diameter:
Joint Electronic Device Engineering Council/jedec/case Outline Designation:         D0-4         Mounting Method:         Threaded stud         Features Provided:         Hermetically sealed case         Overall Width Across Flats:         Between 0.424 inches and 0.437 inches         Thread Size:         0.190 inches         Semiconductor Material:         Silicon         Voltage Rating In Volts Per Characteristic:         100.0 reverse voltage, peak         Current Rating Per Characteristic:         300.00 amperes forward current, average absolute         Maximum Operating Tempurature Per Measurement Point:         200.0 degrees celsius case         Thread Stud and 1 tab, solder lug         Specification Data:         80131-release3851 professional/industrial association specification         Shelf Life:         N/a         Unit of Measure:            Demilitarization:         No	0.424 inches
Joint Electronic Device Engineering Council/jedec/case Outline Designation: D0-4 Mounting Method: Threaded stud Features Provided: Hermetically sealed case Overall Width Across Flats: Between 0.424 inches and 0.437 inches Thread Size: 0.190 inches Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Mounting Facility Quantity:
D0-4 Mounting Method: Threaded stud Features Provided: Hermetically sealed case Overall Width Across Flats: Between 0.424 inches and 0.437 inches Thread Size: 0.190 inches Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 100.0 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	1
Mounting Method: Threaded stud Features Provided: Hermetically sealed case Overall Width Across Flats: Between 0.424 inches and 0.437 inches Thread Size: 0.190 inches Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Joint Electronic Device Engineering Council/jedec/case Outline Designation:
Threaded stud Features Provided: Hermetically sealed case Overall Width Across Flats: Between 0.424 inches and 0.437 inches Thread Size: 0.190 inches Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	D0-4
Features Provided: Hermetically sealed case Overall Width Across Flats: Between 0.424 inches and 0.437 inches Thread Size: 0.190 inches Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Sheff Life: N/a Unit Of Measure:  Demilitarization: No	Mounting Method:
Hermetically sealed case Overall Width Across Flats: Between 0.424 inches and 0.437 inches Thread Size: 0.190 inches Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Sheff Life: N/a Unit Of Measure:  Demilitarization: No	Threaded stud
Overall Width Across Flats: Between 0.424 inches and 0.437 inches Thread Size: 0.190 inches Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Features Provided:
Between 0.424 inches and 0.437 inches Thread Size: 0.190 inches Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Hermetically sealed case
Thread Size: 0.190 inches Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Overall Width Across Flats:
0.190 inches Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization:	Between 0.424 inches and 0.437 inches
Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Thread Size:
Silicon Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.190 inches
Voltage Rating In Volts Per Characteristic: 100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Semiconductor Material:
100.0 reverse voltage, peak Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Silicon
Current Rating Per Characteristic: 300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Voltage Rating In Volts Per Characteristic:
300.00 amperes forward current, average absolute Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	100.0 reverse voltage, peak
Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization:	Current Rating Per Characteristic:
200.0 degrees celsius case Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	300.00 amperes forward current, average absolute
Thread Series Designator: Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Maximum Operating Tempurature Per Measurement Point:
Unf Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	200.0 degrees celsius case
Terminal Type And Quantity: 1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Thread Series Designator:
1 threaded stud and 1 tab, solder lug Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Unf
Specification Data: 80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization:	Terminal Type And Quantity:
80131-release3851 professional/industrial association specification Shelf Life: N/a Unit Of Measure:  Demilitarization: No	1 threaded stud and 1 tab, solder lug
Shelf Life: N/a Unit Of Measure:  Demilitarization: No	Specification Data:
N/a Unit Of Measure:  Demilitarization: No	80131-release3851 professional/industrial association specification
Unit Of Measure:  Demilitarization: No	Shelf Life:
 Demilitarization: No	N/a
Νο	Unit Of Measure:
Νο	
	Demilitarization:
Fiig:	No
	Fiig:
A110a0	A110a0