Diode Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-00-968-6486

Inclosure Material: Glass Overall Length: Between 0.230 inches and 0.300 inches Terminal Length: 1.000 inches Overall Diameter: Between 0.085 inches and 0.107 inches Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-7 Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 150.0 regulator voltage Current Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Sheff Life: N/a Unit Of Measure: Pomillitarization: No Fig: Alt0a0	
Overall Length: Between 0.230 inches and 0.300 inches Terminal Length: 1.000 inches Overall Diameter: Between 0.085 inches and 0.107 inches Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-7 Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 100.0 regulator voltage Current Rating Per Characteristic: 10.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 10.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 10.00 milliamperes celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: Noil 1-release2316 professional/industrial association specification Shift Life: N/a Unit Of Measure: r Pomilitarization: No Fig:	Inclosure Material:
Between 0.230 inches and 0.300 inches Terminal Length: 1.000 inches Overall Diameter: Between 0.085 inches and 0.107 inches Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-7 Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 150.0 regulator voltage Current Rating Per Characteristic: 100 milliamperes repetitive peak forward current Power Rating Per Characteristic: 250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Shef Life: N/a Lift Of Measure: - Demilitarization: No Fig:	
Terminal Length: 1.000 inches Overall Diameter: Between 0.085 inches and 0.107 inches Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-7 Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 150.0 regulator voltage Current Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Sheft Life: N/a Unit of Measure: Demilitarization: Berification Elector	
1.000 inches Overall Diameter: Between 0.085 inches and 0.107 inches Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-7 Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 150.0 regulator voltage Current Rating Per Characteristic: 1.000 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.000 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.000 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.000 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.000 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.000 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.010 milliamperes repetitive peak forward current Poterinetal Type And Quantity: 2 uninsulated wire lead Specification Data: Na Unit Of Measure: Imilliarization:	
Overall Diameter: Between 0.085 inches and 0.107 inches Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-7 Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 150.0 regulator voltage Current Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 1.00 milliamperes celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: Rotf Life: Na Unit Of Measure: - Terminal Type And Quantity: I unit of Measure: - Terminal Type And Quan	-
Between 0.085 inches and 0.107 inches Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-7 Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 150.0 regulator voltage Current Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: Nai Inti Of Measure: Pinal Type And Quantity: Na Pint Of Measure: Pintitarization: No <td></td>	
Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-7 Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 150.0 regulator voltage Current Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: No Init Of Measure: Demilitarization: No	
Do-7 Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 150.0 regulator voltage Current Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 150.0 regulator voltage Current Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Joint Electronic Device Engineering Council/jedec/case Outline Designation:
Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 150.0 regulator voltage Current Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: Na Unit Of Measure: Demilitarization: No Fig:	
Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 150.0 regulator voltage Current Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Pemilitarization: No Fig:	Mounting Method:
Silicon Voltage Rating In Volts Per Characteristic: 150.0 regulator voltage Current Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal
Voltage Rating In Volts Per Characteristic: 150.0 regulator voltage Current Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Semiconductor Material:
 150.0 regulator voltage Current Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Fig: 	Silicon
Current Rating Per Characteristic: 1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	Voltage Rating In Volts Per Characteristic:
1.00 milliamperes repetitive peak forward current Power Rating Per Characteristic: 250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No	150.0 regulator voltage
Power Rating Per Characteristic: 250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Current Rating Per Characteristic:
250.0 milliwatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.00 milliamperes repetitive peak forward current
Maximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadSpecification Data:80131-release2316 professional/industrial association specificationShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig:	Power Rating Per Characteristic:
175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	250.0 milliwatts small-signal input power, common-collector preset
Terminal Type And Quantity: 2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Maximum Operating Tempurature Per Measurement Point:
2 uninsulated wire lead Specification Data: 80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	175.0 degrees celsius ambient air
Specification Data: 80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
80131-release2316 professional/industrial association specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	2 uninsulated wire lead
Shelf Life: N/a Unit Of Measure: Demilitarization: No	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	80131-release2316 professional/industrial association specification
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A110a0	Fiig:
	A110a0