Diode Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-01-003-0795

Inclosure Material: Glass: Versall Length: 0.300 inches: Dorrial Length: 0.375 inches: Overall Diameter: 0.375 inches: Purction For Which Designed: 2.Caner dioda: Purction For Which Designed: 2.Caner dioda: Mounting Method: Terminal Pestures Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 4.5.0 regulator voltage Voltage Tolarance In Percent: 4.5.0 regulator voltage Voltage Tolarance In Percent: 5.0.00 milliamperes all primarias horsepower metric: Power Rating Per Characteristic: 3.0.00 milliamperes all primarias horsepower metric: Paver Rating Per Characteristic: 3.00 milliamperes all primarias horsepower metric: 3.00 milliamperes all prim	
Overall Length:0.300 inchesFerminal Length:0.375 inchesOverall Diameter:0.145 inchesFunction For Which Designed:Zamer diodeMounting Method:TerminalFeatures Provided:Hermetically sealed caseSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:45.0 regulator voltageVoltage Tolerance In Percent:-5.0/+5.0Gurrent Rating Per Characteristic:10.0 milliamperes all primaries horsepower metricPower Rating Per Characteristic:10.0 degrees celsius ambient airIrrenical Type And Quantity:11.0 degrees celsius ambient airPrimei Type And Quantity:12.0 degrees celsius ambient airPower Characteristic:NaNaPower Characteristic:NaPower Characteristic:Power Characteristic:Power Characteristic:Power Characteristic:Power Characteristic:Power Characteristic:Power Characte	Inclosure Material:
0.300 inches Ferminal Length: 0.375 inches 0.975 inches 0.145 inches Function For Which Designed: 2aner diode Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 45.0 regulator voltage Voltage Tolerance In Percent: -5.0/45.0 Current Rating Per Characteristic: 45.0 regulator voltage Power Rating Per Characteristic: 45.0 regulator woltage Power Rating Per Characteristic: 45.0 regulator woltage Power Rating Per Characteristic: 15.0 degrees celsius ambient air Terminal Type And Quantity: 15.0 degrees celsius ambient air Terminal Type And Quantity: 17.0 degrees celsius ambient air Pometication: Na 17.0 degrees celsius ambient air Pometication: Na 17.1 degrees celsius ambient air Pometication:	Glass
Ferminal Length: 0.375 inches Overall Diameter: 0.145 inches Function For Which Designed: Zener diode Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 45.0 regulator voltage Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 15.0 degrees celsius ambient air Terminal Type And Quantity: 12.0 degrees celsius ambient air Prover Rating Per Characteristic: 13.0 degrees celsius ambient air Terminal Type And Quantity: 12.0 degrees celsius ambient air Power Rating Type And Quantity: 13.0 degrees celsius ambient air Forminal Type And Quantity:	Overall Length:
0.975 inches Vorall Diameter: Outsoon For Which Designed: Function For Which Designed: Caneer diode Function For Which Designed: Caneer diode Forminal Features Provided: Ferminal Features Provided: Featu	0.300 inches
Overall Diameter:0.145 inchesFunction For Which Designed:Zener diodeMounting Method:TerminalFeatures Provided:Hermetically sealed caseSemiconductor Material:SiliconVoltage Rating In Volts Per Characteristic:45.0 regulator voltageVoltage Tolerance In Percent:-5.0/+5.0Gurrent Rating Per Characteristic:0.00 milliamperes all primaries horsepower metricPower Rating Per Characteristic:3.0.0 milliamperes all primaries horsepower metricPower Rating Per Characteristic:17.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadShelf Life:NaMatInti Of Measure:Fonilitarization:NoFig:	Terminal Length:
0.145 inches Function For Which Designed: Zener diode Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 45.0 regulator voltage Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 30.0 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 3.0 valts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsultated wire lead Shelf Life: N/a Int Of Measure: - - Pomilitarization: No Fig:	0.975 inches
Function For Which Designed: Zener diode Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 45.0 regulator voltage Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 30.0 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 3.0 valts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsultated wire lead Shelf Life: Na Int Of Measure: - - Pemilitarization: No	Overall Diameter:
Zener diode Mounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 45.0 regulator voltage Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 5.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: Na Unit Of Measure: Fig:	0.145 inches
Hounting Method: Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 45.0 regulator voltage Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Sheff Life: Pomilitarization:	Function For Which Designed:
Terminal Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 45.0 regulator voltage Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 5.0 vatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 unisulated wire lead Shelf Life: N/a Init Of Measure: - Pomilitarization: No Fig:	Zener diode
Features Provided: Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 45.0 regulator voltage Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 30.00 milliamperes all primarius horsepower metric Power Rating Per Characteristic: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: Iva Int Of Measure: - Demiltarization: No Fig:	Mounting Method:
Hermetically sealed case Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 45.0 regulator voltage Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 5.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: Na Inf of Measure: - - Permilitarization: No Fig:	Terminal
Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 45.0 regulator voltage Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 5.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: Na Demilitarization: No Fig:	Features Provided:
Silicon Voltage Rating In Volts Per Characteristic: 45.0 regulator voltage Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 5.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Hermetically sealed case
Voltage Rating In Volts Per Characteristic: 45.0 regulator voltage Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 5.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: Init Of Measure: Pomilitarization: No Fig:	Semiconductor Material:
45.0 regulator voltage Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 5.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	Silicon
Voltage Tolerance In Percent: -5.0/+5.0 Current Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 5.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Voltage Rating In Volts Per Characteristic:
-5.0/+5.0 Current Rating Per Characteristic: 30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 5.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No	45.0 regulator voltage
Current Rating Per Characteristic:30.00 milliamperes all primaries horsepower metricPower Rating Per Characteristic:5.0 watts small-signal input power, common-collector presetMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aInt Of Measure:Demilitarization:NoFig:	Voltage Tolerance In Percent:
30.00 milliamperes all primaries horsepower metric Power Rating Per Characteristic: 5.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-5.0/+5.0
Power Rating Per Characteristic:5.0 watts small-signal input power, common-collector presetMaximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Current Rating Per Characteristic:
5.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	30.00 milliamperes all primaries horsepower metric
Maximum Operating Tempurature Per Measurement Point:175.0 degrees celsius ambient airTerminal Type And Quantity:2 uninsulated wire leadShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Power Rating Per Characteristic:
175.0 degrees celsius ambient air Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	5.0 watts small-signal input power, common-collector preset
Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Maximum Operating Tempurature Per Measurement Point:
2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	175.0 degrees celsius ambient air
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type And Quantity:
N/a Unit Of Measure: Demilitarization: No Fiig:	2 uninsulated wire lead
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	
A110a0	
	A110a0