NSN 5961-01-004-1058

Transistor - Page 1 of 1



breakdown voltage, collector-to-emitter, base open and 4.0 breakdown

| | ransistor - Page 1 of 1 |
|----|---|
| V | iew Online at https://aerobasegroup.com/nsn/5961-01-004-1058 |
| In | nclosure Material: |
| Ρ | lastic |
| 0 | verall Length: |
|). | 190 inches |
| Γ | erminal Length: |
|). | 500 inches |
| C | verall Height: |
|). | 165 inches |
| n | ternal Configuration: |
| l | unction contact |
| Ξ | lectrode Internally-electrically Connected To Case: |
|) | ollector |
| Λ | lounting Method: |
| Ī | erminal |
| 3 | emiconductor Material: |
| S | ilicon |
| / | oltage Rating In Volts Per Characteristic: |
| ļ | 5.0 breakdown voltage, collector-to-base, emitter open and 45.0 |
| (| oltage, emitter-to-base, collector open |
| ; | urrent Rating Per Characteristic: |
| (| 0.00 milliamperes source cutoff current |
|) | ower Rating Per Characteristic: |
| (| 00.0 milliwatts small-signal input power, common-collector |
| - | ransfer Ratio: |
| 4 | 0.0 static forward current transfer ratio, common-emitter |
| M | aximum Operating Tempurature Per Measurement Point: |
| (| 65.0 degrees celsius junction |
| 3 | pecial Features: |
| Jı | unction pattern arrangement: npn |
| Г | erminal Type And Quantity: |
| 3 | uninsulated wire lead |
| s | helf Life: |
| N | /a |
| U | nit Of Measure: |
| | |
| D | emilitarization: |
| N | 0 |
| E | lig: |
| | |