## NSN 5961-01-005-6616

Semiconductor Device Set - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5961-01-005-6616   |
|---|
| Inclosure Material:   |
| Metal all transistor  |
| Overall Length:   |
| 1.330 inches all transistor   |
| Mounting Facility Quantity:   |
| 1 all transistor  |
| Internal Configuration:   |
| Junction contact all transistor   |
| Internal Junction Configuration:  |
| Npn all transistor  |
| Component Function Relationship:  |
| Matched   |
| Component Name And Quantity:  |
| 2 transistor  |
| Mounting Method:  |
| Threaded stud all transistor  |
| Overall Width Across Flats:   |
| 0.667 inches all transistor and 0.687 inches all transistor   |
| Semiconductor Material:   |
| Silicon all transistor  |
| Voltage Rating In Volts Per Characteristic:   |
| 400.0 collector to base voltage/static/emitter open all transistor and 400.0 collector to emitter voltage/static/base open all transistor and 6.5 |
| emitter to base voltage, static, collector open all transistor  |
| Current Rating Per Characteristic:  |
| 10.00 amperes source cutoff current all transistor  |
| Power Rating Per Characteristic:  |
| 100.0 watts small-signal input power, common-collector absolute all transistor  |
| Maximum Operating Tempurature Per Measurement Point:  |
| 150.0 degrees celsius ambient air all transistor  |
| Precious Material And Location:   |
| Die attach with header and cap option gold  |
| Precious Material:  |
| Gold  |
| Test Data Document:   |
| 82577-928272 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;           |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                                       |
| Terminal Type And Quantity:   |
| 3 tab, solder lug all transistor  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |

No

Demilitarization:

## NSN 5961-01-005-6616

Semiconductor Device Set - Page 2 of 2



Fiig:

A110a0