NSN 5961-01-028-7067

Thyristor Semiconductor Device - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5961-01-028-7067 **Inclosure Material:** Metal **Overall Length:** 1.646 inches **Mounting Facility Quantity: Internal Configuration:** Junction contact **Mounting Method:** Threaded stud **Features Provided:** Hermetically sealed case **Overall Width Across Flats:** Between 0.544 inches and 0.563 inches **Thread Size:** 0.250 inches **Semiconductor Material:** Silicon **Voltage Rating In Volts Per Characteristic:** 200.0 repetitive peak reverse voltage and 300.0 nonrepetitive peak reverse voltage and 5.0 peak gate voltage **Current Rating Per Characteristic:** 16.00 amperes forward current, average absolute and 150.00 amperes peak forward surge current absolute **Maximum Operating Tempurature Per Measurement Point:** 125.0 degrees celsius ambient air **Special Features:** Junction pattern arrangement: pnpn **Test Data Document:** 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator: Terminal Type And Quantity:** 1 threaded stud and 2 tab, solder lug **Specification Data:** 81349-mil-prf-19500/108 government specification Shelf Life: N/a **Unit Of Measure:**

A110a0

No Fiig:

Demilitarization:

NSN 5961-01-028-7067

Thyristor Semiconductor Device - Page 2 of 2



Mil-std (military Standard):

Mil-prf-19500 spec.