NSN 5961-01-044-5840

Transistor - Page 1 of 1

Fiig: A110a0



View Online at https://aerobasegroup.com/psn/5061-01-044-5840

| View Online at https://aerobasegroup.com/nsn/5961-01-044-5840 |
|--|
| Inclosure Material: |
| Metal |
| Overall Length: |
| Between 0.170 inches and 0.210 inches |
| Terminal Length: |
| 0.500 inches |
| Overall Diameter: |
| Between 0.209 inches and 0.230 inches |
| Internal Configuration: |
| Field effect |
| Electrode Internally-electrically Connected To Case: |
| Gate |
| Mounting Method: |
| Terminal |
| Terminal Circle Diameter: |
| 0.100 inches |
| Features Provided: |
| Hermetically sealed case |
| Semiconductor Material: |
| Silicon |
| Voltage Rating In Volts Per Characteristic: |
| 40.0 drain to gate voltage and 20.0 drain to source voltage and -40.0 gate to source voltage |
| Current Rating Per Characteristic: |
| 10.00 milliamperes gate current and 8.00 milliamperes zero-gate-voltage drain current |
| Power Rating Per Characteristic: |
| 360.0 milliwatts total power dissipation |
| Maximum Operating Tempurature Per Measurement Point: |
| 175.0 degrees celsius ambient air |
| Test Data Document: |
| 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 3 uninsulated wire lead |
| Specification Data: |
| 81349-mil-s-19500/431 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |