NSN 5961-01-051-5791

Transistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5961-01-051-5791

| View Online at https://aerobasegroup.com/nsn/5961-01-051-5791 |
|--|
| Inclosure Material: |
| Metal |
| Overall Length: |
| 1.252 inches |
| Overall Height: |
| 0.340 inches |
| Overall Width: |
| 0.700 inches |
| Mounting Facility Quantity: |
| 2 |
| Internal Configuration: |
| Junction contact |
| Joint Electronic Device Engineering Council/jedec/case Outline Designation: |
| To-213aa |
| Electrode Internally-electrically Connected To Case: |
| Collector |
| Mounting Method: |
| Unthreaded hole |
| Features Provided: |
| Hermetically sealed case |
| Semiconductor Material: |
| Silicon |
| Voltage Rating In Volts Per Characteristic: |
| -80.0 collector to base voltage/static/emitter open and -80.0 collector to emitter voltage/static/base open and -7.0 emitter to base voltage, |
| static, collector open |
| Current Rating Per Characteristic: |
| Between -2.00 amperes source cutoff current and -4.00 amperes source cutoff current |
| Power Rating Per Characteristic: |
| 25.0 watts small-signal input power, common-collector preset |
| Maximum Operating Tempurature Per Measurement Point: |
| 200.0 degrees celsius junction |
| Special Features: |
| Junction pattern arrangement: pnp |
| Test Data Document: |
| 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead and 1 case |
| Specification Data: |
| 81349-mil-prf-19500/441 government specification |
| Shelf Life: |

N/a

Unit Of Measure:

NSN 5961-01-051-5791

Transistor - Page 2 of 2



| _ | | | | | |
|----|-----|---------|-----|---|--|
| 11 | em) | tor | 172 | n | |
| | | | | | |

No

Fiig:

A110a0

Mil-std (military Standard):

Mil-prf-19500 spec.