

View Online at https://aerobasegroup.com/nsn/5961-01-072-1460

Overall Length:1.140 inchesOverall Height:0.400 inchesOverall Width:1.140 inches1.140 inchesCircuit Connection Style Designator:Bridge 1 phaseAbsolute Maximum Voltage Rating In Volts Per Characteristic:100.0 peak inverse voltageAbsolute Maximum Current Rating Per Characteristic:25.00 amperes average forward current averaged over a full 60-hz cycleMounting Method:Unthreaded holeMaterial:Silicon
Overall Height:0.400 inchesOverall Width:1.140 inchesCircuit Connection Style Designator:Bridge 1 phaseAbsolute Maximum Voltage Rating In Volts Per Characteristic:100.0 peak inverse voltageAbsolute Maximum Current Rating Per Characteristic:25.00 amperes average forward current averaged over a full 60-hz cycleMounting Method:Unthreaded holeMaterial:
0.400 inches Overall Width: 1.140 inches Circuit Connection Style Designator: Bridge 1 phase Absolute Maximum Voltage Rating In Volts Per Characteristic: 100.0 peak inverse voltage Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Unthreaded hole Material:
Overall Width: 1.140 inches Circuit Connection Style Designator: Bridge 1 phase Absolute Maximum Voltage Rating In Volts Per Characteristic: 100.0 peak inverse voltage Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Unthreaded hole Material:
 1.140 inches Circuit Connection Style Designator: Bridge 1 phase Absolute Maximum Voltage Rating In Volts Per Characteristic: 100.0 peak inverse voltage Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Unthreaded hole Material:
Circuit Connection Style Designator: Bridge 1 phase Absolute Maximum Voltage Rating In Volts Per Characteristic: 100.0 peak inverse voltage Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Unthreaded hole Material:
Bridge 1 phase Absolute Maximum Voltage Rating In Volts Per Characteristic: 100.0 peak inverse voltage Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Unthreaded hole Material:
Absolute Maximum Voltage Rating In Volts Per Characteristic: 100.0 peak inverse voltage Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Unthreaded hole Material:
 100.0 peak inverse voltage Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Unthreaded hole Material:
Absolute Maximum Current Rating Per Characteristic: 25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Unthreaded hole Material:
25.00 amperes average forward current averaged over a full 60-hz cycle Mounting Method: Unthreaded hole Material:
Mounting Method: Unthreaded hole Material:
Unthreaded hole Material:
Material:
Silicon
Silicon
Terminal Type And Quantity:
4 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A503j0