Thyristor Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-01-072-8584

Inclosure Material:

Metal

Overall Length:

1.125 inches

Mounting Facility Quantity:

1

Mounting Method:

Threaded stud

Features Provided:

Hermetically sealed case

Overall Width Across Flats:

Between 1.031 inches and 1.062 inches

Thread Size:

0.500 inches

Semiconductor Material:

Silicon

Voltage Rating In Volts Per Characteristic:

140.0 off-state voltage, rms total and 10.0 off-state voltage, peak and 5.0 gate voltage, dc

Current Rating Per Characteristic:

2.00 amperes forward current, total rms of standard range and 50.00 amperes forward current, total rms megahertz

Power Rating Per Characteristic:

5.0 watts small-signal input power, common-collector blank

Maximum Operating Tempurature Per Measurement Point:

125.0 degrees celsius ambient air

Test Data Document:

81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Terminal Type And Quantity:

3 uninsulated wire lead w/terminal lug

Specification Data:

81349-mil-prf-19500 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A110a0

Mil-std (military Standard):

Mil-prf-19500 spec.