## NSN 5961-01-078-9494

Transistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-01-078-9494

Inclosure Material: Plastic Plastic Overall Length: Between 0.120 inches and 0.240 inches Terminal Length: 0.500 inches Internal Configuration: Field effect Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 25.0 breakdown voltage, gate-to-source, with all other terminals short-circuited to source Current Rating Per Characteristic: 50.00 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demillitarization: No
Overall Length:         Between 0.120 inches and 0.240 inches         Terminal Length:         0.500 inches         Internal Configuration:         Field effect         Mounting Method:         Terminal         Semiconductor Material:         Silicon         Voltage Rating In Volts Per Characteristic:         25.0 breakdown voltage, gate-to-source, with all other terminals short-circuited to source         Current Rating Per Characteristic:         30.00 milliamperes source cutoff current minor         Power Rating Per Characteristic:         350.00 milliwatts small-signal input power, common-collector absolute         Maximum Operating Tempurature Per Measurement Point:         125.0 degrees celsius ambient air         Terminal Type And Quantity:         6 uninsulated wire lead         Sheff Life:         N/a         Unit of Measure:         Image:         Image:         Image:         Image:         Image:         Bornisulated wire lead         Sheff Life:         N/a         Image:         Image:         Image:         Image:         Image:         Image:
Between 0.120 inches and 0.240 inches Terminal Length: 0.500 inches Internal Configuration: Field effect Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 25.0 breakdown voltage, gate-to-source, with all other terminals short-circuited to source Current Rating Per Characteristic: 350.00 milliamperes source cutoff current minor Power Rating Per Characteristic: 350.00 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit of Measure:
Terminal Length: 0.500 inches Internal Configuration: Field effect Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 25.0 breakdown voltage, gate-to-source, with all other terminals short-circuited to source Current Rating Per Characteristic: 50.00 milliamperes source cutoff current minor Power Rating Per Characteristic: 350.0 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit of Measure:  Demilitarization:
0.500 inches Internal Configuration: Field effect Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 25.0 breakdown voltage, gate-to-source, with all other terminals short-circuited to source Current Rating Per Characteristic: 50.00 milliamperes source cutoff current minor Power Rating Per Characteristic: 350.0 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Init Of Measure: 
Internal Configuration: Field effect Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 25.0 breakdown voltage, gate-to-source, with all other terminals short-circuited to source Current Rating Per Characteristic: 50.00 milliamperes source cutoff current minor Power Rating Per Characteristic: 350.0 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization:
Field effect         Mounting Method:         Terminal         Semiconductor Material:         Silicon         Voltage Rating In Volts Per Characteristic:         25.0 breakdown voltage, gate-to-source, with all other terminals short-circuited to source         Current Rating Per Characteristic:         30.00 milliamperes source cutoff current minor         Power Rating Per Characteristic:         350.0 milliwatts small-signal input power, common-collector absolute         Maximum Operating Tempurature Per Measurement Point:         125.0 degrees celsius ambient air         Terminal Type And Quantity:         6 uninsulated wire lead         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:
Mounting Method: Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 25.0 breakdown voltage, gate-to-source, with all other terminals short-circuited to source Current Rating Per Characteristic: 50.00 milliamperes source cutoff current minor Power Rating Per Characteristic: 350.0 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure: 
Terminal Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 25.0 breakdown voltage, gate-to-source, with all other terminals short-circuited to source Current Rating Per Characteristic: 50.00 milliamperes source cutoff current minor Power Rating Per Characteristic: 350.0 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air 125.0 degrees celsius ambient air ferminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization:
Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 25.0 breakdown voltage, gate-to-source, with all other terminals short-circuited to source Current Rating Per Characteristic: 50.00 milliamperes source cutoff current minor Power Rating Per Characteristic: 350.0 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure: 
Silicon Voltage Rating In Volts Per Characteristic: 25.0 breakdown voltage, gate-to-source, with all other terminals short-circuited to source Current Rating Per Characteristic: 50.00 milliamperes source cutoff current minor Power Rating Per Characteristic: 350.0 milliwatts small-signal input power, common-collector absolute 350.0 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization:
Voltage Rating In Volts Per Characteristic: 25.0 breakdown voltage, gate-to-source, with all other terminals short-circuited to source Current Rating Per Characteristic: 50.00 milliamperes source cutoff current minor Power Rating Per Characteristic: 350.0 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization:
25.0 breakdown voltage, gate-to-source, with all other terminals short-circuited to source Current Rating Per Characteristic: 50.00 milliamperes source cutoff current minor Power Rating Per Characteristic: 350.0 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization:
Current Rating Per Characteristic: 50.00 milliamperes source cutoff current minor Power Rating Per Characteristic: 350.0 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization:
50.00 milliamperes source cutoff current minor Power Rating Per Characteristic: 350.0 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure: 
Power Rating Per Characteristic: 350.0 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure: 
350.0 milliwatts small-signal input power, common-collector absolute Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization:
Maximum Operating Tempurature Per Measurement Point: 125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization:
125.0 degrees celsius ambient air Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization:
Terminal Type And Quantity: 6 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization:
6 uninsulated wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization:
Shelf Life: N/a Unit Of Measure:  Demilitarization:
N/a Unit Of Measure:  Demilitarization:
Unit Of Measure:  Demilitarization:
 Demilitarization:
Fiig:
A110a0