## NSN 5961-01-101-2344

Diode Semiconductor Device - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5961-01-101-2344 **Inclosure Material:** Metal **Overall Length:** 0.570 inches **Terminal Length:** Between 1.000 inches and 1.625 inches **Overall Diameter:** Between 0.215 inches and 0.235 inches **Function For Which Designed:** Transient suppressor Joint Electronic Device Engineering Council/jedec/case Outline Designation: Do-13 **Electrode Internally-electrically Connected To Case:** Cathode **Mounting Method: Terminal Features Provided:** Hermetically sealed case **Semiconductor Material:** Silicon Voltage Rating In Volts Per Characteristic: 7.13 breakdown voltage, dc and 7.88 breakdown voltage, dc and 6.00 working peak reverse voltage **Current Rating Per Characteristic:** 10.00 milliamperes source cutoff current horsepower metric **Power Rating Per Characteristic:** 1.0 watts small-signal input power, common-collector horsepower metric **Maximum Operating Tempurature Per Measurement Point:** 175.0 degrees celsius ambient air **Test Data Document:** 81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead **Specification Data:** 81349-mil-s-19500/507 government specification Shelf Life: N/a **Unit Of Measure:** 

A110a0

No Fiig:

Demilitarization:

## NSN 5961-01-101-2344

Diode Semiconductor Device - Page 2 of 2



Mil-std (military Standard):

Mil-prf-19500 spec.