NSN 5961-01-104-7522

Transistor - Page 1 of 2



| Inclosure Material: Metal Overall Length: 1.573 inches Terminal Length: Between 0.312 inches and 0.500 inches Overall Melght: Between 0.350 inches and 0.500 inches Overall Melght: Between 0.350 inches and 0.500 inches Overall Width: 1.505 inches Mounting Facility Quantity: 2 Internal Configuration: Junction coniact Electrode Internally-electrically Connected To Case: Collector Mounting Method: Unithreaded hole Semiconductor Material: Silicon Voltage Rating in Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Maximum Operating Tempurature Per Moasurement Point: 200.0 degrees celsius junction Special Features: Maximum Operating Tempurature Per Moasurement Point: 201.0 degrees celsius junction Special Features: Maximum Operating Tempurature Per Moasurement Point: 202.0 degrees celsius junction Special Features: Maximum Operating Tempurature Per Moasurement Point: 203.0 degrees celsius junction Special Features: Maximum Operating Tempurature Per Moasurement Point: 204.0 degrees celsius junction Special Features: Maximum Operating Tempurature Per Moasurement Point: 205.0 degrees celsius junction Special Features: Maximum Operating Tempurature Per Moasurement Point: 206.0 degrees celsius junction Special Features: Maximum Operating Tempurature Per Moasurement Point: 207.0 degrees celsius junction Special Features: Maximum Operating Tempurature Per Moasurement Point: 208.0 degrees celsius junction Special Features: Maximum Operating Tempurature Per Moasurement Point: 209.0 degrees celsius junction Special Features: Maximum Operating Tempurature Per Moasurement Point: 200.0 degrees celsius junction Special Features: Ma | View Online at https://aerobasegroup.com/nsn/5961-01-104-7522 |
|--|--|
| Overall Length: 1.573 Inches Terminal Length: Between 0.372 inches and 0.500 Inches Overall Height: Between 0.350 inches and 0.300 Inches Overall Height: 1.050 Inches Mounting Facility Quantity: 2 Internal Configuration: Junction contact Electrode Internally-electrically Connected To Case: Collector Mounting Method: Unthreaded hole Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: 81.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 11.5.0 waits small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: rpn Test Data Document: 81.349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', 'average', '", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81.349-mil-s-19500/456 government specification Sheff Life: No | Inclosure Material: |
| 1.573 inches Terminal Length: Between 0.312 inches and 0.500 inches Overall Height: Between 0.250 inches and 0.360 inches Overall Width: 1.050 inches Mounting Facility Quantity: 2 Internal Configuration: Junction contact Electrode Internally-electrically Connected To Case: Collector Mounting Method: Unthreaded hole Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/statio/emitter open and 80.0 collector to emitter voltage/statio/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-a-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-a-19500/456 government specification Sheff Life: No | Metal |
| Terminal Length: Between 0.312 inches and 0.500 inches Overall Height: Between 0.250 inches and 0.360 inches Overall Width: 1.050 inches Mounting Facility Quantity: 2 Internal Configuration: Junction contact Electrode Internally-electrically Connected To Case: Collector Mounting Method: Unthreaded hole Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector paners source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Sheff Life: N/a | Overall Length: |
| Between 0.312 inches and 0.500 inches Overall Width: 1.050 inches Mounting Facility Quantity: 2 Internal Configuration: Junction contact Electrode Internally-electrically Connected To Case: Collector Mounting Method: Unthreaded hole Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: 815 owatts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 20.0 degrees celsius junction Special Features: Unoction pattern arrangement: npn Test Data Document: 81349-mill-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mill-s-19500/456 government specification Sheft Life: N/a | 1.573 inches |
| Overall Height: Between 0.250 inches and 0.360 inches Overall Wildth: 1.050 inches Mounting Facility Quantity: 2 Internal Configuration: Junction contact Between 0.250 inches Internally-electrically Connected To Case: Collector Mounting Method: Unthreaded hole Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: 80.0 collector to passe voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: 81.50 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81.349-mill-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81.349-mil-s-19500/456 government specification Shelf Lite: N/a | Terminal Length: |
| Between 0.250 inches and 0.360 inches Overall Width: 1.050 inches Mounting Facility Quantity: 2 Internal Configuration: Junction contact Electrode Internally-electrically Connected To Case: Collector Mounting Method: Unthreaded hole Semiconductor Material: Silicon Voltage Rating in Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: 81.50 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81.349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Between 0.312 inches and 0.500 inches |
| Overall Width: 1.050 inches Mounting Facility Quantity: 2 Internal Configuration: Junction contact Electrode Internally-electrically Connected To Case: Collector Mounting Method: Unthreaded hole Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 131:349-mils-s19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', 'average', '", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 131:439-mils-19500/456 government specification Shelf Life: N/a | Overall Height: |
| Mounting Facility Quantity: 2 Internal Configuration: Junction contact Electrode Internally-electrically Connected To Case: Collector Mounting Method: Unthreaded hole Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mils-s19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mils-s19500/456 government specification Shelf Life: N/a | Between 0.250 inches and 0.360 inches |
| Mounting Facility Quantity: Internal Configuration: Junction contact Electrode Internally-electrically Connected To Case: Collector Mounting Method: Unthreaded hole Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 waits small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mils-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mils-19500/456 government specification Shelf Life: N/a | Overall Width: |
| Internal Configuration: Junction contact Electrode Internally-electrically Connected To Case: Collector Mounting Method: Unthreaded hole Semiconductor Material: Silicon Voltage Rating in Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | 1.050 inches |
| Internal Configuration: Junction contact Electrode Internally-electrically Connected To Case: Collector Mounting Method: Unthreaded hole Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: 815.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Sheft Life: N/a | Mounting Facility Quantity: |
| Junction contact Electrode Internally-electrically Connected To Case: Collector Mounting Method: Unthreaded hole Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | 2 |
| Electrode Internally-electrically Connected To Case: Collector Mounting Method: Unthreaded hole Semiconductor Material: Sillicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Internal Configuration: |
| Collector Mounting Method: Unthreaded hole Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Junction contact |
| Mounting Method: Unthreaded hole Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Electrode Internally-electrically Connected To Case: |
| Unthreaded hole Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Collector |
| Semiconductor Material: Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Mounting Method: |
| Silicon Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Unthreaded hole |
| Voltage Rating In Volts Per Characteristic: 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Semiconductor Material: |
| 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Silicon |
| static, collector open Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Voltage Rating In Volts Per Characteristic: |
| Current Rating Per Characteristic: Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | 80.0 collector to base voltage/static/emitter open and 80.0 collector to emitter voltage/static/base open and 5.0 emitter to base voltage, |
| Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | static, collector open |
| Power Rating Per Characteristic: 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Current Rating Per Characteristic: |
| 115.0 watts small-signal input power, common-collector preset Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Between 7.50 amperes source cutoff current and 20.00 amperes source cutoff current |
| Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: | Power Rating Per Characteristic: |
| 200.0 degrees celsius junction Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | 115.0 watts small-signal input power, common-collector preset |
| Special Features: Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Maximum Operating Tempurature Per Measurement Point: |
| Junction pattern arrangement: npn Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | 200.0 degrees celsius junction |
| Test Data Document: 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Special Features: |
| 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Junction pattern arrangement: npn |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Test Data Document: |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| Terminal Type And Quantity: 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| 1 case and 2 pin Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: 81349-mil-s-19500/456 government specification Shelf Life: N/a | Terminal Type And Quantity: |
| 81349-mil-s-19500/456 government specification Shelf Life: N/a | 1 case and 2 pin |
| Shelf Life: N/a | Specification Data: |
| N/a | 81349-mil-s-19500/456 government specification |
| | Shelf Life: |
| Unit Of Measure: | N/a |
| | Unit Of Measure: |

N

Demilitarization:

NSN 5961-01-104-7522 Transistor - Page 2 of 2



Fiig:

A110a0