# NSN 5961-01-107-0963

Transistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5961-01-107-0963

# Inclosure Material:

Metal

**Overall Length:** 

1.573 inches

# **Overall Height:**

0.328 inches

# **Overall Width:**

1.050 inches

# Mounting Facility Quantity:

2

### Internal Configuration:

Junction contact-darlington connected

### Joint Electronic Device Engineering Council/jedec/case Outline Designation:

#### To-3

### Electrode Internally-electrically Connected To Case:

Collector

#### Mounting Method:

Unthreaded hole

### Features Provided:

Hermetically sealed case

### Semiconductor Material:

Silicon

### Voltage Rating In Volts Per Characteristic:

-80.0 collector to base voltage/static/emitter open and -80.0 collector to emitter voltage/static/base open and -5.0 emitter to base voltage, static, collector open

# Current Rating Per Characteristic:

Between -0.20 amperes source cutoff current and -12.00 amperes source cutoff current

### **Power Rating Per Characteristic:**

150.0 watts small-signal input power, common-collector preset

# Maximum Operating Tempurature Per Measurement Point:

175.0 degrees celsius ambient air

# **Special Features:**

Junction pattern arrangement: pnp

# Test Data Document:

81349-mil-prf-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

1 case and 2 pin

# **Specification Data:**

81349-mil-prf-19500/501 government specification

# Shelf Life:

N/a

# Unit Of Measure:

# NSN 5961-01-107-0963

Transistor - Page 2 of 2



# Demilitarization:

Yes - demil/mli

Fiig:

A110a0

# Mil-std (military Standard):

Mil-prf-19500 spec.