Photo Semiconductor Device - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5961-01-129-1967

Inclosure Material:
Metal and glass
Overall Length:
Between 0.170 inches and 0.210 inches
Terminal Length:
1.500 inches
Overall Diameter:
Between 0.209 inches and 0.230 inches
End Application:
T-39a 99999
Internal Configuration:
Field effect
Mounting Method:
Terminal
Terminal Circle Diameter:
0.100 inches
Features Provided:
Hermetically sealed case
Semiconductor Material:
Silicon
Voltage Rating In Volts Per Characteristic:
Voltage Rating In Volts Per Characteristic: 15.0 drain to source voltage and 15.0 drain to gate voltage
15.0 drain to source voltage and 15.0 drain to gate voltage
15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic:
 15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic: 50.00 milliamperes gate current
 15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic: 50.00 milliamperes gate current Power Rating Per Characteristic:
 15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic: 50.00 milliamperes gate current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation
 15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic: 50.00 milliamperes gate current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point:
 15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic: 50.00 milliamperes gate current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction
 15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic: 50.00 milliamperes gate current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Terminal Type And Quantity:
 15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic: 50.00 milliamperes gate current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Terminal Type And Quantity: 4 uninsulated wire lead
 15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic: 50.00 milliamperes gate current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Terminal Type And Quantity: 4 uninsulated wire lead Shelf Life:
 15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic: 50.00 milliamperes gate current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Terminal Type And Quantity: 4 uninsulated wire lead Shelf Life: N/a
 15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic: 50.00 milliamperes gate current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Terminal Type And Quantity: 4 uninsulated wire lead Shelf Life: N/a
 15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic: 50.00 milliamperes gate current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Terminal Type And Quantity: 4 uninsulated wire lead Shelf Life: N/a Unit Of Measure:
15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic: 50.00 milliamperes gate current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Terminal Type And Quantity: 4 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization:
15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic: 50.00 milliamperes gate current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Terminal Type And Quantity: 4 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: Yes - demil/mli
15.0 drain to source voltage and 15.0 drain to gate voltage Current Rating Per Characteristic: 50.00 milliamperes gate current Power Rating Per Characteristic: 300.0 milliwatts total device dissipation Maximum Operating Tempurature Per Measurement Point: 200.0 degrees celsius junction Terminal Type And Quantity: 4 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Pemilitarization: Yes - demil/mli Fiig: